



Reservedele til

CONVOTHERM


2017




heating elements

immersion heating elements

3 hole flange ø47.5mm




vm nr.	415931	Ref. No.	5007076 5007076K
description	heating element 12000W 220V mounting ø 47.5mm heating circuits 3 L 585mm W 28mm H 28mm number of thermostat sleeves 1 thermostat sleeves ø 6.5mm length thermostat sleeves 170mm thermostat sleeve clinging tube ø 6.3mm hole distance 63mm hole ø 8mm cable length 950mm 3 hole flange immersion heater		
For models:	OD20.20, OS20.20, OSC20.20, OSP20.20		
accessories for	415931		
	vm nr.	510408	Ref. No. 6005015
	O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs		
	vm nr.	510562	Ref. No. —
	O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs		



vm nr.	415803	Ref. No.	5007062 5007062K
description	heating element 6000W 230V mounting ø 47.5mm heating circuits 3 L 325mm W 26mm H 38mm number of thermostat sleeves 1 thermostat sleeves ø 6mm length thermostat sleeves 160mm thermostat sleeve clinging tube ø 6.3mm hole distance 62mm hole ø 8mm cable length 790mm connection cable 3 hole flange immersion heater		
For models:	OD10.10, OD10.20, OS10.10, OS10.20, OSC10.10, OSC10.20, OSP10.10, OSP10.20		
spare parts for	415803		
	vm nr.	510408	Ref. No. 6005015
	O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs		
accessories for	415803		
	vm nr.	510562	Ref. No. —
	O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs		

1

vm nr.	415802	Ref. No.	5007071 5007071K 8007071
description	heating element 9000W 230V mounting ø 47.5mm heating circuits 3 L 385mm W 35mm H 46mm number of thermostat sleeves 1 thermostat sleeves ø 6mm length thermostat sleeves 160mm thermostat sleeve clinging tube ø 8.5mm hole distance 62mm hole ø 8mm cable length 800mm 3 hole flange immersion heater		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP6.10		
accessories for	415802		
	vm nr.	510562	Ref. No. —
	O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs		



miscellaneous



vm nr.	420042	Ref. No.	2619180 5017003
description	heating element 13200W 230V heating circuits 3 L 545mm W 65mm H 33mm number of thermostat sleeves 1 thermostat sleeves ø 8mm length thermostat sleeves 160mm tube ø 8.5mm hole distance 71mm hole ø 7mm cable length 1000mm flange connection immersion heater flange width 57mm flange length 88mm		
For models:	OEB20.20, OES20.20		



vm nr.	417733	Ref. No.	5056321
description	heating element 13300W 230V heating circuits 3 L 275mm W 35mm H 70mm number of thermostat sleeves 2 thermostat sleeves ø 3.5/8mm length thermostat sleeves 120/140mm thermostat sleeve eccentric, clinging tube ø 8.5mm hole distance 67mm hole ø 8mm combi-steamer flange width 82mm flange length 82mm with gasket and nut		



vm nr.	420043	Ref. No.	2619178 5017001
description	heating element 6600W 230V heating circuits 3 L 275mm W 65mm H 37mm number of thermostat sleeves 1 thermostat sleeves ø 7.8mm length thermostat sleeves 150mm tube ø 8.5mm hole distance 71mm hole ø 7mm cable length 1050mm flange connection immersion heater flange width 57mm flange length 88mm		
For models:	OEB10.10, OEB10.20, OEB6.20, OES10.10, OES10.20, OES6.20		
accessories for	420043		
	vm nr.	550992	Ref. No. 6015023
	gasket L 87mm W 57mm hole ø 6mm hole distance 70/40mm 4 holes thickness 3mm suitable for CONVOTHERM		

1

			
vm nr.	417601	Ref. No.	2619187
description	heating element 6600W 230V heating circuits 3 L 275mm W 70mm H 25mm hole distance 40x70mm hole ø 6.5mm cable length 1050mm tube ø 8.5mm flange length 87mm flange width 56mm thermostat sleeves ø 6mm number of thermostat sleeves 1 length thermostat sleeves 170mm		
For models:	OEB10.10, OEB10.20, OEB6.20, OES10.10, OES10.20, OES6.20		
accessories for	417601		
			
vm nr.	550992	Ref. No.	6015023
gasket L 87mm W 57mm hole ø 6mm hole distance 70/40mm 4 holes thickness 3mm suitable for CONVOTHERM			

			
1			
vm nr.	417734	Ref. No.	5056320
description	heating element 9000W 230V heating circuits 3 L 210mm W 40mm H 70mm number of thermostat sleeves 2 thermostat sleeves ø 3.5/8mm length thermostat sleeves 119/139mm thermostat sleeve eccentric, clinging tube ø 8.5mm hole distance 67mm hole ø 8mm flange combi-steamer flange width 82mm flange length 82mm		

			
1			
vm nr.	417719	Ref. No.	2619188 5017013
description	heating element 9900W 230V heating circuits 3 L 415mm W 52mm H 37mm number of thermostat sleeves 1 thermostat sleeves ø 7.5mm length thermostat sleeves 160mm thermostat sleeve eccentric, clinging tube ø 8.5mm hole distance 71mm hole ø 7mm 4 hole flange immersion heater flange width 57mm flange length 88mm		



1

vm nr.	418685	Ref. No.	2619179 5017002
description	heating element 9900W 230V heating circuits 3 L 415mm W 65mm H 37mm number of thermostat sleeves 1 thermostat sleeves ø 6.5mm length thermostat sleeves 160mm tube ø 8.5mm hole distance 72mm hole ø 7mm flange width 58mm flange length 88mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES6.10, OES6.20		
accessories for	418685		
	vm nr.	550992	Ref. No. 6015023
 gasket L 87mm W 57mm hole ø 6mm hole distance 70/40mm 4 holes thickness 3mm suitable for CONVOTHERM			

1 1/2"				
1 				
vm nr.	415874	Ref. No.	5007067 5007068 5007068K	
description	heating element 12000/14300W 220/240V heating circuits 3 thread 1 1/2" L 585mm W 40mm H 30mm thermostat sleeves ø 6.5mm length thermostat sleeves 160mm thermostat sleeve eccentric, clinging tube ø 6.3mm cable length 750mm connection cable immersion heater flange with thread hole distance 63mm mounting ø 47.5mm hole ø 8/10mm number of thermostat sleeves 1			
For models:	HUD20.20			
accessories for	415874			
	vm nr.	510424	Ref. No.	—
gasket copper ED ø 55mm ID ø 48mm thickness 2.2mm Centellen for thread 1 1/2"				
	vm nr.	520211	Ref. No.	—
reducer thread 2" ET - 1 1/2" IT brass				
	vm nr.	520212	Ref. No.	—
hexagonal nut thread 1 1/2" brass WS 60 H 8mm				
	vm nr.	550361	Ref. No.	—
blind flange ø 58mm thread 1 1/2"				



1				
vm nr.	415500	Ref. No.	5007061 5007061K 5007063 5007063K	
description	heating element 7500W 220V heating circuits 3 thread 1½" L 435mm W 33mm H 25mm tube ø 6.3mm cable length 780mm immersion heater flange with thread			
For models:	HUD10.10			
accessories for	415500			
	vm nr.	510406	Ref. No.	6005065
	flat gasket fibre ED ø 60mm ID ø 48mm thickness 3mm for thread 1½" Qty 1 pcs			
	vm nr.	510424	Ref. No.	—
	gasket copper ED ø 55mm ID ø 48mm thickness 2.2mm Centellen for thread 1½"			
	vm nr.	520211	Ref. No.	—
	reducer thread 2" ET - 1½" IT brass			
	vm nr.	520212	Ref. No.	—
	hexagonal nut thread 1½" brass WS 60 H 8mm			
	vm nr.	550361	Ref. No.	—
	blind flange ø 58mm thread 1½"			



1

			
vm nr.	415501	Ref. No.	5007066 5007066K
description	heating element 9000W 230V heating circuits 3 thread 1½" L 430mm W 32mm H 26mm tube ø 6.3mm cable length 820mm connection cable immersion heater flange with thread		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		
accessories for	415501		
	vm nr.	510406	Ref. No. 6005065
	flat gasket fibre ED ø 60mm ID ø 48mm thickness 3mm for thread 1½" Qty 1 pcs		
	vm nr.	510424	Ref. No. —
	gasket copper ED ø 55mm ID ø 48mm thickness 2.2mm Centellen for thread 1½"		
	vm nr.	520211	Ref. No. —
	reducer thread 2" ET - 1½" IT brass		
	vm nr.	520212	Ref. No. —
	hexagonal nut thread 1½" brass WS 60 H 8mm		
	vm nr.	550361	Ref. No. —
	blind flange ø 58mm thread 1½"		

heating elements for convection

1

vm nr.	420524	Ref. No.	2625104K 2630606
description	heating element 10200W 230V heating circuits 3 ID ø 250mm ED ø 320mm L 350mm H 58mm L1 70mm H1 8mm H2 58mm flange length 90mm flange width 70mm tube ø 8.5mm threaded		

1

vm nr.	420558	Ref. No.	5056330
description	heating element 10500W 230V heating circuits 3 ID ø 400mm ED ø 417mm L 472mm H 100mm H1 15mm H2 83mm flange length 90mm flange width 70mm hole distance 55mm connection M5 tube ø 8.5mm cable length 180mm convection heating element flange for combi-steamer series CONVOTHERM 4		

			
1			
vm nr.	418684	Ref. No.	2619192 5017005
description	heating element 10500W 230V heating circuits 3 ID ø 402mm ED ø 420mm L 475mm H 100mm L1 55mm W1 29mm H1 25mm H2 75mm flange length 90mm flange width 70mm hole distance 74mm connection M5 tube ø 8.5mm convection heating element mounting thread M5 rectangular flange with bolt		
For models:	OEB6.10, OES6.10		

			
1			
vm nr.	417718	Ref. No.	5007035 5007035K 5030625
description	heating element 12000W 220V heating circuits 3 ID ø 387mm ED ø 400mm L 430mm H 90mm H1 23mm H2 67mm thread M14 3 hole fixing connection male faston tube ø 6.5mm mounting pos. outer for combi-steamer		

1

vm nr.	415385	Ref. No.	5007036 5007036K
description	heating element 15000W 220V heating circuits 3 ID ø 390mm ED ø 405mm L 435mm H 110mm L1 22mm W1 300mm H1 22mm H2 84mm thread M14x1.5 6 hole fixing connection M5 tube ø 8.5mm convection heating element		
For models:	OD10.10, OD20.10, OS10.10, OS20.10, OSC10.10, OSC20.10, OSP10.10, OSP20.10		
accessories for	415385		
	vm nr.	361182	Ref. No. —
nut thread 1/4" H 5mm nickel-plated brass WS 17 Qty 1 pcs			
	vm nr.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
	vm nr.	520228	Ref. No. —
tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			
	vm nr.	550262	Ref. No. —
flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			


			
1			
vm nr.	418886	Ref. No.	5007038 5007038K 5007042K
description	heating element 18000W 380V heating circuits 3 ID ø 380mm ED ø 393mm L 435mm H 120mm L1 50mm H1 15mm thread M14x1.5 screw mounting tube ø 6.5mm convection heating element		
For models:	AR72, HUD10.10, HUD20.10, UG10.10, UG20.10		

			
1			
vm nr.	418768	Ref. No.	2619181 5017004
description	heating element 18900W 230V heating circuits 3 ID ø 467mm ED ø 484mm L 545mm H 99mm L1 6mm W1 28mm H1 14mm H2 85mm flange length 90mm flange width 70mm connection M4 connection length 112mm tube ø 8.5mm convection heating element with counterflange and cable		
For models:	OEB10.10, OEB20.10, OEB6.20, OES10.10, OES20.10, OES6.20		

			
1			
vm nr.	418876	Ref. No.	2619190 5017016
description	heating element 18900W 230V heating circuits 3 ID ø 470mm ED ø 486mm L 540mm H 100mm L1 48mm H1 27mm H2 73mm flange length 90mm flange width 70mm hole distance 55mm connection M5 connection length 115mm tube ø 8.5mm convection heating element		
For models:	OEB10.10, OEB20.10, OEB6.20, OES10.10, OES20.10, OES6.20		

			
1			
vm nr.	420557	Ref. No.	5056331
description	heating element 18900W 230V heating circuits 3 ID ø 470mm ED ø 487mm L 540mm H 100mm H1 16mm H2 83mm flange length 90mm flange width 70mm hole distance 55mm connection M5 tube ø 8.5mm cable length 1300mm convection heating element flange connection for combi-steamer series CONVOTHERM 4		

			
1			
vm nr.	420559	Ref. No.	5056332
description	heating element 2x16500W 230V heating circuits 6 ID ø 485mm ED ø 570mm L 590mm H 134mm H1 22mm H2 108mm flange length 175mm flange width 105mm hole distance 80mm connection length M5mm tube ø 8.5mm cable length 1500mm convection heating element flange for combi-steamer series CONVOTHERM		

			
1			
vm nr.	415129	Ref. No.	5007044 5007044K
description	heating element 30000W		
For models:	HUD12.20, HUD20.20, OD12.20, OD20.10, OD20.20, OS12.20, OS20.20, OSC12.20, OSC20.20, OSP12.20, OSP20.20		
spare parts for	415129		
	vm nr.	415899	Ref. No. —
	heating element 15000W 220V heating circuits 3 ID ø 437mm ED ø 454mm L 475mm H 98mm L1 18mm W1 305mm H1 19mm H2 79mm thread M14x1.5 6 hole fixing connection M5 tube ø 8.5mm mounting pos. inner convection heating element		
	vm nr.	415906	Ref. No. —
	heating element 15000W 220V heating circuits 3 ID ø 558mm ED ø 575mm L 605mm H 100mm L1 30mm W1 300mm H1 25mm H2 80mm thread M14x1.5 6 hole fixing connection M5 tube ø 8.5mm mounting pos. outer convection heating element		

			
1			
vm nr.	419102	Ref. No.	2619177 5017000
description	heating element 33000W 230/400V heating circuits 6 ID ø 480mm ED ø 570mm L 590mm H 140mm flange length 175mm flange width 105mm		
For models:	OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20		

			
1			
vm nr.	419233	Ref. No.	2618805
description	heating element 5400W 230V heating circuits 2 ID ø 252mm ED ø 269mm L 297mm H 62mm L1 11mm W1 65mm H1 12mm H2 50mm flange length 100mm flange width 22mm hole distance 87mm connection 6.3x0.8 tube ø 8.5mm for combi-steamer mounting thread M5 with mounting accessories OES6.06 Mini P3		

			
1			
vm nr.	420156	Ref. No.	2123634 2625181 5017084
description	heating element 6800W 230V heating circuits 2 ID ø 250mm ED ø 265mm L 300mm H 65mm L1 38mm H1 7mm H2 56mm flange length 90mm flange width 70mm connection male faston 6.3mm connection length 77mm tube ø 8.5mm convection heating element flange connection		
accessories for	420156		
	vm nr.	521013	Ref. No. 2623226 6015025
gasket set suitable for CONVOTHERM for heating element L 90mm W 71mm Qty 1m graphite hole distance 54/74mm			

1

vm nr.	415384	Ref. No.	5007033 5007033K
description	heating element 9000W 230V heating circuits 3 ID ø 390mm ED ø 403mm L 440mm H 88mm L1 30mm W1 300mm H1 18mm H2 70mm thread M14x1.5 6 hole fixing connection M5 convection heating element		
For models:	AR28, AR40, OD10.10, OD10.20, OD6.10, OS6.10, OSC6.10, OSP6.10		
spare parts for	415384		
	vm nr.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
accessories for	415384		
	vm nr.	520228	Ref. No. —
tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			
	vm nr.	520230	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs			
	vm nr.	521101	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 SS Qty 1 pcs			
	vm nr.	550262	Ref. No. —
flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			

			
1			
vm nr.	420075	Ref. No.	5007022
description	mounting set suitable for convection heating element		
For models:	AR100, AR108, AR28, AR30, AR40, AR50, AR54, AR72, HUD10.10, HUD20.10, HUD6.10, OD10.10, OD20.10, OD6.10, OS10.10, OS6.10, OSC10.10, OSC6.10, OSP10.10, OSP6.10, UG10.10, UG20.10, UG6.10		

			
1			
vm nr.	692737	Ref. No.	2623227 6015024
description	mounting set suitable for for combi-steamer L 175mm W 105mm mounting pos. CONVOTHERM		

thermostats

bi-metal thermostats

bi-metal thermostats



vm nr.	391049	Ref. No.	5056372
description	bi-metal thermostat hole distance 24mm switch-off temp. 80°C 1NC 1-pole 10A 250V connection F6.3x0.8 suitable for CONVOTHERM		

control and safety thermostats

EGO

control thermostats

55.10/19_ series



vm nr.	375631	Ref. No.	5001032
description	thermostat t.max. 249°C temperature range 55-249°C 1-pole 1NO 16A probe ø 3.1mm probe L 226mm capillary pipe 1270mm capillary pipe isolated 850mm gland nut 3/8"-M8x1 shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 318°		
For models:	OD10.20, OD12.20		

55.13_ series



vm nr.	375116	Ref. No.	5001021 5001021K 5001040
description	thermostat t.max. 258°C temperature range 58-258°C 1-pole 1NC 16A probe ø 3.1mm probe L 201mm capillary pipe 1130mm capillary pipe isolatedmm gland nut shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 270°		
For models:	AR100, AR108, AR12, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, AR8, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		

safety thermostats

55.13_ series



vm nr.	375731	Ref. No.	5001026 5001026+6005081 5001026K
description	safety thermostat switch-off temp. 135°C 1-pole 1NC 16A probe ø 6mm probe L 77mm capillary pipe 520mm capillary pipe isolatedmm gland nut probe SS		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		



vm nr.	375117	Ref. No.	5001030 5001030K 51021
description	safety thermostat switch-off temp. 325°C 1-pole 16A probe ø 4mm probe L 91mm capillary pipe 390mm capillary pipe isolatedmm gland nut probe SS		
For models:	OD10.10, OD10.20, OD6.10		



vm nr.	390126	Ref. No.	5001029 5001029K
description	safety thermostat switch-off temp. 340°C 1-pole 1NC 16A probe ø 3.1mm probe L 201mm capillary pipe 1170mm capillary pipe isolatedmm gland nut probe SS		
For models:	AR108, AR72, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

55.32_ series



vm nr.	375392	Ref. No.	5001039
description	safety thermostat switch-off temp. 360°C 3-pole 1CO/2NC 20A probe ø 4mm probe L 120mm capillary pipe 1490mm capillary pipe isolated 1450mm gland nut probe SS		
For models:	AR12, AR18, AR28, AR40, AR54, AR8, OES6.06		



vm nr.	375474	Ref. No.	5001031
description	safety thermostat t.max. 340°C switch-off temp. 340°C 2-pole 1NC/1CO 1x20/1x0.5A probe ø 4mm probe L 120mm capillary pipe 1300mm capillary pipe isolated 900mm gland nut probe		
For models:	OD10.10, OD10.20, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20		

56._ series



vm nr.	381480	Ref. No.	5056319
description	safety thermostat switch-off temp. 170°C temperature range 14-170°C 1-pole 16A probe ø 6mm probe L 65mm capillary pipe 1460mm capillary pipe isolated 1400mm probe material SS 230V		



vm nr.	376061	Ref. No.	5056329
description	safety thermostat switch-off temp. 340°C 1-pole 16A probe ø 3mm probe L 160mm capillary pipe 1200mm capillary pipe isolated 1140mm		

accessories

fitting parts



vm nr.	550389	Ref. No.	4006041
description	bracket for contact thermostat		
For models:	HUD12.20, HUD20.20		



vm nr.	550388	Ref. No.	4006031
description	bracket for contact thermostat mounting distance 24.5mm mounting ø 3.8		
For models:	HUD10.10, HUD20.10, HUD20.20, OD10.20, OD12.20		

gland nut accessories

ducts



vm nr.	550148	Ref. No.	6005080
description	gland duct ET M12x0.75 IT M9x1 probe ø max. 6.5mm WS 17 silicone		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS12.20, OS20.10, OS20.20, OSC12.20, OSC20.10, OSC20.20, OSP12.20, OSP20.10, OSP20.20		

gaskets



vm nr.	699830	Ref. No.	6015026
description	gasket silicone ø 10mm L 8mm		

switches and momentary switches

cam switches

on/off



1

vm nr.	301282	Ref. No.	5003022
description	cam switch sequence 0-1 shaft $\varnothing$ 6x4.6mm shaft L 19.5mm 4-pole rotation 45°		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

5 operating positions



1

vm nr.	301277	Ref. No.	5003023
description	cam switch 5 operating positions 7NO sequence 0-1-2-3-4 16A shaft $\varnothing$ 6x4.6mm shaft L 19mm connection male faston 6.3mm plastic		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

magnetic switches


28.5x19mm




1

vm nr.	348210	Ref. No.	5056328
description	magnetic switch L 28.5mm W 19mm cable length 450mm PIC MS-328/980A 5214 suitable for CONVOTHERM		

29x19mm



vm nr.	345117	Ref. No.	5003075 5013070
description	magnetic switch L 28.5mm W 19mm 1NO 250V 0.04A P max. 10W connection cable cable length 1000mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20...(Other models you can see in the webshop)		




vm nr.	345217	Ref. No.	5003082
description	magnetic switch L 29mm W 19mm 1NO 125V 0.5A P max. 10W connection cable cable length 2000mm		



1

vm nr.	347495	Ref. No.	2518798
description	magnetic switch L 29mm W 19mm 1NO 250V 0.3A P max. 10W connection cable cable length 2000mm PIC		
For models:	OES6.06		

M10x0.75




1

vm nr.	345632	Ref. No.	5003079
description	magnetic switch thread M10x0.75 1NO 250V 0.5A P max. 50W connection cable cable length 2000mm type 102		
For models:	OD10.20, OD12.20, OD20.20, OSG10.10, OSG12.20, OSG20.20, OSG6.10		
accessories for	345632		
	vm nr.	100779	Ref. No.
	nut thread M10x0.75 H 3mm WS 14 SS Qty 2 pcs		

accessories

magnets



1


vm nr.	345700	Ref. No.	5003076
description	magnet ømm L 29mm H 6.5mm W 19mm hole distance 16mm M3 hole ø 3.5mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSP6.10		

control equipment

RAFI

Lumotast series

fascias



vm nr.	345140	Ref. No.	5003054
description	bezel clear		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10		

momentary push switches



vm nr.	345139	Ref. No.	5003053
description	momentary push switch mounting measurements ø16mm 230V 1NC/1NO		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10		
accessories for	345139		
	vm nr.	345140	Ref. No.
	bezel clear		
	vm nr.	346719	Ref. No.
	bezel yellow		
	vm nr.	346720	Ref. No.
	bezel rectangular green		
	vm nr.	346721	Ref. No.
	bezel rectangular red		
	vm nr.	359590	Ref. No.
	light bulb socket T5.5K 24V 3W ø 5.5mm L 22mm clear		
	vm nr.	359591	Ref. No.
	light bulb socket T5.5K 48V 3W ø 5.5mm L 22mm clear		
	vm nr.	359592	Ref. No.
	light bulb socket T5.5K 12V 3W ø 5.5mm L 22mm clear		
	vm nr.	359593	Ref. No.
	light bulb socket T5.5K 60V 0.02A		

TELEMECANIQUE (EFA)

XB4 series

rotary switches



1

vm nr.	347383	Ref. No.	5003031 5003031K 5003035
description	switch mounting measurements ø22mm 2NO 0-1 latching		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10		

encoders and potentiometers



1

vm nr.	300268	Ref. No.	5056359
description	encoder rotation 360° 0.01A shaft ø 6x5.5mm shaft L 17mm connection for ribbon cable for combi-steamer thread M10x0.75 5V CONVOTHERM 4 0.1Ohm EBE CESI 32/LS		



1

vm nr.	300098	Ref. No.	5009095
description	potentiometer		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

lamps

indicator lights

indicator lights 3-piece (housing, lens and bulb)

lamps

light bulbs



1

vm nr.	359055	Ref. No.	5003046
description	light bulb socket T1 1/2 12VW 0.08A ø 4.9mm L 13mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

indicator lights (complete)

ø16mm

with plug-in socket



1

vm nr.	362003	Ref. No.	5004026
description	indicator light ø 16mm yellow connection F6.3 temp.-resist. 120°C		

screw-on/push-on fit

light bulbs

for ovens



1

vm nr.	359458	Ref. No.	2618779
description	light bulb socket E14 15W 230V with gasket		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	359610	Ref. No.	5005040 5005040K
description	light bulb t.max. 300°C socket E14 15W 230V ø 22mm L 47mm lens L 20mm for oven lamp type Philips		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		



1

vm nr.	359612	Ref. No.	5005045
description	light bulb t.max. 300°C socket E14 25W 230V ø 25mm L 56mm lens L 30mm for oven lamp type Philips		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB6.10, OES6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

for indicator lights



1

vm nr.	359055	Ref. No.	5003046
description	light bulb socket T1 1/2 12VW 0.08A ø 4.9mm L 13mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		



oven lamps

universal oven lamps

mounting diameter 35.5mm



1

vm nr.	359720	Ref. No.	5005012
description	oven lamp mounting ø 35.5mm 230V 15W socket E14 temp.-resist. 300°C connection male faston 6.3mm hard glas		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		
spare parts for	359720		
	vm nr.	359701	Ref. No. 5005016
	lamp socket socket E14 220-230V mounting ø 35.5mm connection male faston 6.3mm 15W		
	vm nr.	359705	Ref. No. 5005017 5005017K 5030620
	oven lamp glass thr.ø 33.5mm ø 52mm hard glas temp.-resist. 350°C		
	vm nr.	359721	Ref. No. 5005025
	gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs		
	vm nr.	359740	Ref. No. —
	light bulb t.max. 300°C socket E14 15W 230V ø 22mm L 48mm lens L 20mm for oven lamp IMPORT		



1

vm nr.	359705	Ref. No.	5005017 5005017K 5030620
description	oven lamp glass thr.ø 33.5mm ø 52mm hard glas temp.-resist. 350°C		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		
accessories for	359705		
	vm nr.	359610	Ref. No. 5005040 5005040K
	light bulb t.max. 300°C socket E14 15W 230V ø 22mm L 47mm lens L 20mm for oven lamp type Philips		
	vm nr.	359700	Ref. No. —
	gasket for pizza oven fibre glass ID ø 32.5mm ED ø 55mm thickness 5mm		
	vm nr.	359721	Ref. No. 5005025
	gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs		
	vm nr.	359837	Ref. No. —
	gasket ID ø 33mm ED ø 46mm thickness 1mm graphite		
	vm nr.	359838	Ref. No. —
	gasket ID ø 33mm ED ø 45mm		



1

vm nr.	359721	Ref. No.	5005025
description	gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		

55x70mm



1


vm nr.	360730	Ref. No.	5056316
description	gasket		
accessories for	360730		
	vm nr.	359596	Ref. No. —
	halogen lamp socket G4 12V 10W temp.-resist. 500°C		
	vm nr.	360728	Ref. No. 5056317
	lamp cover complete L 99.5mm W 84.5mm H 8.5mm mounting distance 68/83mm		
	vm nr.	360729	Ref. No. 5056315
	lamp socket socket G4 with cable		



1

vm nr.	360728	Ref. No.	5056317
description	lamp cover complete L 99.5mm W 84.5mm H 8.5mm mounting distance 68/83mm		
accessories for	360728		
	vm nr.	359596	Ref. No. —
	halogen lamp socket G4 12V 10W temp.-resist. 500°C		
	vm nr.	360729	Ref. No. 5056315
	lamp socket socket G4 with cable		
	vm nr.	360730	Ref. No. 5056316
	gasket		

			
1			
vm nr.	359297	Ref. No.	5015003 5015006
description	frame L 95mm W 81mm mounting distance 68/83mm thickness 6mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		
accessories for	359297		
	vm nr.	359299	Ref. No. —
	gasket L 91mm W 77mm hole ø 3mm for oven lamp		

			
1			
vm nr.	359296	Ref. No.	5015002
description	lamp glass L 74mm W 58mm thickness 3mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

producer-specific oven lamps

CONVOTHERM

			
1			
vm nr.	358180	Ref. No.	6015018 6015020
description	gasket L 94mm W 78mm PTFE thickness 3mm for oven lamp		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

			
1			
vm nr.	360728	Ref. No.	5056317
description	lamp cover complete L 99.5mm W 84.5mm H 8.5mm mounting distance 68/83mm		
accessories for	360728		
	vm nr.	359596	Ref. No. —
	halogen lamp socket G4 12V 10W temp.-resist. 500°C		

accessories for	360728		
	vm nr.	360729	Ref. No. 5056315
	lamp socket socket G4 with cable		
	vm nr.	360730	Ref. No. 5056316
	gasket		

			
1			
vm nr.	694335	Ref. No.	5015005
description	lamp glass L 87mm W 72mm thickness 3mm		

			
1			
vm nr.	359488	Ref. No.	2618780
description	oven lamp complete mounting measurements 55x70mm 230V 15W socket E14 rectangular connection male faston 6.3mm L 87mm W 70mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		
spare parts for	359488		
	vm nr.	358180	Ref. No. 6015018 6015020
	gasket L 94mm W 78mm PTFE thickness 3mm for oven lamp		
	vm nr.	359297	Ref. No. 5015003 5015006
	frame L 95mm W 81mm mounting distance 68/83mm thickness 6mm		
	vm nr.	359299	Ref. No. —
	gasket L 91mm W 77mm hole ø 3mm for oven lamp		
	vm nr.	694335	Ref. No. 5015005
	lamp glass L 87mm W 72mm thickness 3mm		

			
1			
vm nr.	692171	Ref. No.	5005020
description	frame for lamp lenses bore ø 6.3mm D1 ø 72mm D2 ø 56mm L 83mm W 83mm thickness 1mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
vm nr.	359643	Ref. No.	5005022
description	lamp glass ø 69mm thickness 4mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
vm nr.	358174	Ref. No.	5005022K
description	lamp glass ø 69mm thickness 4mm with gasket		

			
vm nr.	360629	Ref. No.	2628501
description	oven lamp incl. gasket mounting ø 10mm 12V 10W socket G4 CONVOTHERM temp.-resist. 300°C		
spare parts for	360629		
	vm nr.	359596	Ref. No.
			—
	 halogen lamp socket G4 12V 10W temp.-resist. 500°C		

			
vm nr.	360680	Ref. No.	2628500
description	oven lamp incl. gasket mounting ø 10mm 12V 10W socket G4 CONVOTHERM temp.-resist. 300°C		
spare parts for	360680		
	vm nr.	359596	Ref. No.
			—
	 halogen lamp socket G4 12V 10W temp.-resist. 500°C		

lamps

light bulbs

			
vm nr.	359610	Ref. No.	5005040 5005040K
description	light bulb t.max. 300°C socket E14 15W 230V ø 22mm L 47mm lens L 20mm for oven lamp type Philips		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		

			
vm nr.	359612	Ref. No.	5005045
description	light bulb t.max. 300°C socket E14 25W 230V ø 25mm L 56mm lens L 30mm for oven lamp type Philips		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB6.10, OES6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

sockets

G4 / G5,3 / G6,35

			
vm nr.	360729	Ref. No.	5056315
description	lamp socket socket G4 with cable		
accessories for	360729		
	vm nr.	359596	Ref. No.
			—
	 halogen lamp socket G4 12V 10W temp.-resist. 500°C		
	vm nr.	360728	Ref. No.
			5056317
	 lamp cover complete L 99.5mm W 84.5mm H 8.5mm mounting distance 68/83mm		
	vm nr.	360730	Ref. No.
			5056316
	 gasket		

timers

mechanical timers

			
vm nr.	350023	Ref. No.	5001003 5001003K
description	timer M2 2-pole operation time 90min impulse mechanical 2CO at 250V 16A permanent position no shaft ø 6x4.6mm shaft flat 6x4.6mm shaft L 23mm mounting distance 28mm connection lateral		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		
accessories for	350023		
	vm nr.	110366	Ref. No.
			—
	 knob switch zero mark t.max. °C ø 44mm shaft ø 6x4.6mm shaft flat upper black		

			
1			
vm nr.	350112	Ref. No.	5001001 5001001K
description	timer M2 2-pole operation time 90min impulse mechanical 2NO at 250V 16A permanent position no shaft ø 6x4.6mm shaft 6x4.6mm shaft L 23mm mounting distance 28mm connection rear		
For models:	AR100, AR108, AR12, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, AR8, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		

alarm devices

buzzers

			
1			
vm nr.	350050	Ref. No.	5003050
description	buzzer 230VAC connection male faston 6.3mm screw mounting thread M4 60dB		

contactors

BENEDIKT & JÄGER

power contactors

			
1			
vm nr.	381476	Ref. No.	5056963
description	power contactor resistive load 130A 230 (AC3/400V) 37kW main contacts 3NO connection screw type K3-74A00		

			
1			
vm nr.	380774	Ref. No.	5056373A
description	power contactor resistive load 32A 230VAC (AC3/400V) 18A/7.5kW main contacts 3NO auxiliary contacts 1NO connection screw connection type K3-18ND10		

			
1			
vm nr.	380775	Ref. No.	5056962
description	power contactor resistive load 65A 230VAC (AC3/400V) 32A/15kW main contacts 3NO auxiliary contacts connection screw connection type K3-32A00230		

auxiliary contacts

			
1			
vm nr.	381456	Ref. No.	5056966
description	auxiliary contact contacts 1NC/1NO AC15 3A connection screw type HKA11		

			
1			
vm nr.	380678	Ref. No.	5056965
description	auxiliary contact contacts 1NO AC15 10A for contactors K2/K3 connection screw type HN10 AC1 25A		

GENERAL ELECTRIC (AEG)

power contactors

			
1			
vm nr.	380247	Ref. No.	4001020 4001020K 4001027 4011000
description	power contactor resistive load 25A 400VAC (AC3/400V) 9A/4kW main contacts 3NO auxiliary contacts 1NC connection screw connection type AEG LS4K 01A type GE CL00A 301		
For models:	AR108, AR28, HUD10.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20...(Other models you can see in the webshop)		



1

vm nr.	380265	Ref. No.	4001041 4011013K
description	power contactor resistive load 60A 230VAC (AC3/400V) 32A/16kW main contacts 3NO auxiliary contacts 1NO connection screw connection type AEG LS15K 00A type GE CL04A 310 H 98mm L 87mm W 55mm		
For models:	AR108, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

auxiliary contacts



1

vm nr.	380269	Ref. No.	4001072
description	auxiliary contact contacts 1NC AC15 6A for contactors CL+LS_K connection screw AC-12 10A type AEG HS07K 01 type GE BCLF 01		
For models:	HUD10.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		



1

vm nr.	380268	Ref. No.	4001070
description	auxiliary contact contacts 1NO for contactors CL+LS_K connection screw AC-12 10A type AEG HS07K 10 type GE BCLF 10		
For models:	HUD20.20		

TELEMECANIQUE (Schneider Electric)

power contactors



1

vm nr.	381204	Ref. No.	4011000K
description	power contactor resistive load 20A 230VAC (AC3/400V) 9A/4kW main contacts 3NO auxiliary contacts 1NO/1NC connection spring terminal type LC1D093P7 with RC circuit LAD4RCU		



1

vm nr.	381342	Ref. No.	4011001 4011001K 4030609
description	power contactor resistive load 25A 230VAC (AC3/400V) 18A/7.5kW main contacts 3NO auxiliary contacts 1NO/1NC connection elastic terminals type LC1D183P7		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20		



1

vm nr.	380952	Ref. No.	4001015 4001030 4001030K
description	power contactor resistive load 40A 230VAC (AC3/400V) 25A/11kW main contacts 4NO auxiliary contacts 1NO/1NC connection screw connection type LC1DT40P7		
For models:	AR100, AR108, AR12, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10, UG10.10, UG20.10, UG6.05		

ABL SURSUM

motor protection circuit breakers



1

vm nr.	380300	Ref. No.	4002034
description	motor protection circuit breaker type Mbs25-016 setting range 1-1.6A (AC3/400V) 0.55kW		
For models:	HUD10.10, HUD20.10, HUD6.10, OD10.10, OD10.20, OD12.20, OD6.10, UG10.20, UG20.20		
accessories for	380300		
	vm nr.	380305	Ref. No. 4002039
	auxiliary contact contacts 1NO/1NC HMS11		



1

vm nr.	380301	Ref. No.	4002035
description	motor protection circuit breaker type Mbs25-025 setting range 1.6-2.5A (AC3/400V) 1.1kW		
For models:	AR18, AR28, AR40, AR54, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		



1

vm nr.	380302	Ref. No.	4002036
description	motor protection circuit breaker type Mbs25-040 setting range 2.5-4A (AC3/400V) 1.5kW		
For models:	OD10.10, OD10.20, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		



1

vm nr.	380322	Ref. No.	4002032
description	motor protection circuit breaker type SFK0E setting range 0.63-1A (AC3/400V) 0.5kW GENERAL ELECTRIC		
For models:	AR108, AR28, AR40, AR54, AR72, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG20.10, UG6.10		

accessories



1

vm nr.	380305	Ref. No.	4002039
description	auxiliary contact contacts 1NO/1NC HMS11		
For models:	HUD12.20, HUD20.20, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

solid state relays

CRYDOM



1

vm nr.	403868	Ref. No.	5056381
description	solid state relay CRYDOM 1 phase 90A 480V 4-32VDC L 58mm W 44mm screw type CWD4890P		

relays

power relays

with flange mounting





1

vm nr.	380131	Ref. No.	4000017
description	power relays Italiana Relè 230VAC 16A 3CO connection male faston 6.3mm screw mounting manuf. no. B2-3-230AC		



with male contacts


female contact 2.0mm



1

vm nr.	380377	Ref. No.	4000022
description	power relays FINDER 220-240VAC 10A 2CO connection F2 plug-in connection manuf. no. 55.32.8.230.0000 94.92.3 250V		
For models:	OD10.20, OD12.20		
accessories for	380377		
	vm nr.	380341	Ref. No. —
	relay socket 4-pole contacts 12 300V voltage AC 6A Italiana Relè manuf. no. ZMD4		
	vm nr.	380378	Ref. No. —
	relay socket 2-pole 55/85 dimensions 70.5x30x27mm 250V voltage AC 10A FINDER manuf. no. 94.72		
	vm nr.	380384	Ref. No. —
	relay socket 2-pole contacts male faston 2.8mm 250V voltage AC 10A W 23mm for		
	vm nr.	380399	Ref. No. —
	relay socket 4-pole dimensions 76.2x27x86.1mm 250V voltage AC 1A FINDER manuf. no. 94.94.3		

plug-in/print relays



1

vm nr.	381090	Ref. No.	4000012
description	print relay 12VDC at 250V 10A with relay socket		
spare parts for	381090		
	vm nr.	380500	Ref. No. —
	print relay 12VDC 2CO at 250V 8A connection pins raster size 5mm REIPOL		

miscellaneous



1

vm nr.	381091	Ref. No.	4000013
description	print relay 230V voltage AC at 250V 10A with relay socket		
For models:	OD10.10, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

transformers

power supplies



1

vm nr.	402981	Ref. No.	5056385
description	power supply primary 100-240VAC secondary 12VDC 60VA secondary 5A H 38mm L 99mm W 155mm connection screw 50/60Hz type ABL1REM12050 combi-steamer P3-devices		

probes

producer-specific probes

probes



1

vm nr.	400024	Ref. No.	5009050
description	temperature probe NTC 100kOhm cable PVC probe -40 up to +125°C cable -10 up to 100°C connection plug thread M10 probe ø6x120mm cable length 0.1m		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10		



1

vm nr.	379409	Ref. No.	5001035
description	temperature probe Pt100 cable PVC probe -100 up to 450°C cable -10 up to 100°C connection 2-wire thread M10 probe ø3x60mm cable length 0.7m		
For models:	OD10.10, OD10.20, OD12.20, OD20.20, OD6.10		

			
vm nr.	379104	Ref. No.	5009052
description	temperature probe Pt100 cable silicone probe -50 up to +300°C cable -50 up to +200°C connection 2-wire thread M10 probe ø4.5x-20mm cable length 3m		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSP10.20, OSP12.20		
accessories for	379104		
			
vm nr.	510416	Ref. No.	6005016
	flat gasket fibre ED ø 19mm ID ø 10.5mm thickness 1.5mm for thread M10 Qty 1 pcs		


			
vm nr.	379105	Ref. No.	5001022 5001023
description	temperature probe Pt100 cable silicone probe -50 up to +600°C cable -50 up to +180°C connection 2-wire thread M14x1.5 probe ø3x350mm cable length 2.4m		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

			
vm nr.	379414	Ref. No.	2219137 5002064
description	temperature probe thermocouple K (NiCr-Ni) cable PTFE probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø1.5x60mm cable length 4m		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

			
vm nr.	379410	Ref. No.	5001015
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread M10 probe ø3x125mm cable length 1.5m		
For models:	OSG10.10, OSG12.20, OSG20.20, OSG6.10		

			
vm nr.	379420	Ref. No.	5001016
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread M10 probe ø3x70mm cable length 0.7m		
For models:	OSG10.10, OSG12.20, OSG20.20, OSG6.10		

			
1			
vm nr.	379800	Ref. No.	5002100 5002100K 5002101 5016014K 5030618
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread M5 probe ø4x20mm cable length 3m		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG20.20, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		
accessories for	379800		
	vm nr.	521012	Ref. No. 6005260
gasket graphite ED ø 15mm ID ø 5mm thickness 1.2mm Qty 1 pcs			

			
vm nr.	402164	Ref. No.	5002102 5002102K 5030619
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread M8 probe ø3x130/230mm cable length 2.1m		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
vm nr.	379536	Ref. No.	5016003
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø1.5x230mm cable length 2m		
For models:	OEB20.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

1

vm nr.	379440	Ref. No.	5002103 5016017
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø1.5x35mm cable length 1.6m		
For models:	OS10.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

1

vm nr.	379751	Ref. No.	5002104
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø1.5x35mm cable length 2.8m		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OS10.10, OS12.20, OS20.10, OS20.20, OSC10.10, OSC12.20, OSC20.10, OSC20.20, OSP10.10, OSP12.20, OSP20.10, OSP20.20		

1

vm nr.	378655	Ref. No.	5056324
description	temperature probe thermocouple K (NiCr-Ni) probe -50 up to 1150°C cable -50 up to +180°C connection coded plug thread M5 probe ø4x20mm cable length 3.2m		

1

vm nr.	381488	Ref. No.	5056323
description	temperature probe thermocouple K (NiCr-Ni) probe -50 up to 1150°C cable -50 up to +180°C thread 2-wire cable length 2.3m		

core probes

1

vm nr.	379828 ¹	Ref. No.	5002068K
description	core temperature probe 3 point probe cable PTFE probe -40 up to +250°C cable -40 up to +250°C connection 5-wire probe ø4x100mm cable length 4m handle ø 12mm handle length 75mm		

¹multipoint probe

1

vm nr.	379428 ¹	Ref. No.	5013022K 5030638 5030676
description	core temperature probe 3 point probe cable PTFE probe -50 up to 1150°C cable -40 up to +250°C connection 5-wire probe ø3x100mm thread cable length 3m handle ø 11mm handle length 75mm		

¹multipoint probe

1

vm nr.	378536	Ref. No.	5056325
description	core temperature probe 4 point probe cable plastic probe -40 up to +250°C cable -40 up to +250°C connection plug probe ø3.5x100mm thread 5/8" cable length 3m handle ø 11mm handle length 75mm		

1

vm nr.	379103	Ref. No.	5002062 5002062K
description	core temperature probe Pt100 cable PTFE probe -40 up to +250°C cable -40 up to +250°C connection 2-wire probe ø4x100mm thread cable length 4m handle ø 15mm handle length 85mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG6.10		

1

vm nr.	379416	Ref. No.	5002066 5002066K
description	core temperature probe Pt100 cable SS corrugated hose probe -40 up to +250°C cable -40 up to +250°C connection 2-wire probe ø3x100mm thread M15x1 cable length 3m handle ø 12mm handle length 85mm		
For models:	OD6.10		

1

vm nr.	381458	Ref. No.	5064012
description	probe 1 point probe cable PTFE connection -40 up to +250 cable length 1.04m handle ø 11mm handle length 72mm		

1

vm nr.	381459	Ref. No.	5064010
description	probe 1 point probe cable PTFE probe -40 up to +250°C connection plug probe ø1.5x60mm handle ø 11mm handle length 70mm		

accessories

plugs/bushes

1

vm nr.	378653	Ref. No.	5064011
description	female connector 2-pole max. 9A protection IP50 chrome-plated brass		

electronics


frequency converters

1

vm nr.	403211	Ref. No.	5014000
description	frequency converter 90-264V L 150mm W 120mm H 100mm output frequency 0-100Hz 550W input frequency 47-63Hz type LVOF550		
For models:	OGB10.10, OGB20.10, OGB6.10, OGB6.20, OGS10.10, OGS20.10, OGS6.10, OGS6.20		

PCBs

			
1			
vm nr.	403686	Ref. No.	5019301
description	control 5010 IDM module P3+mini 5010 IDM module P3+mini		

			
1			
vm nr.	404007	Ref. No.	5019105 5019304
description	control PCB combi-steamer OEB10.10 control 5010		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

1


vm nr.	402882	Ref. No.	5019100 5019306 5019406 5019418 5019420
description	control PCB combi-steamer OEx xx.xx L 280mm W 100mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		
accessories for	402882		
	vm nr.	403078	Ref. No. 5019011
software suitable for CONVOTHERM Update-Box P3			
	vm nr.	403686	Ref. No. 5019301
control 5010 IDM module P3+mini 5010 IDM module P3+mini			

			
1			
vm nr.	403794	Ref. No.	5019150
description	control PCB for combi-steamer OES6.06 Mini P3 L 465mm W 95mm model ST5020-BM V5.19		

			
1			
vm nr.	402587	Ref. No.	5009017
description	control PCB L 320mm W 118mm cable length 500mm supply 5/12VDC		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

			
1			
vm nr.	402588	Ref. No.	5009303
description	keypad PCB combi-steamer OS10.10 L 322mm W 117mm buttons 11		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
1			
vm nr.	402589	Ref. No.	5019101 5019300 CM5019300
description	keypad PCB combi-steamer P3-devices L 337mm W 132mm buttons 14		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	403870	Ref. No.	5056362
description	keypad PCB for combi-steamer CONVOTHERM 4 with cable ON-OFF		



1

vm nr.	402879	Ref. No.	5009302
description	keypad PCB L 118mm W 69mm suitable for convection oven buttons 8		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	402910	Ref. No.	5009310 5009317
description	PCB		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	402207	Ref. No.	5009305
description	PCB combi-steamer OS10.10		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	402208	Ref. No.	5009300
description	PCB combi-steamer OS10.10		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	401877	Ref. No.	5009005 5009006 5009007 5009008 5009029 5009029K
description	power PCB combi-steamer OD10.10 suitable for CONVOTHERM with mounting accessories		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		



1

vm nr.	402586	Ref. No.	5009018
description	power PCB L 252mm W 120mm model 28755329 230V 0.1A voltage AC		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

			
1			
vm nr.	402637	Ref. No.	2619973 5009301 5019154 5019305
description	power supply combi-steamer conversion kit		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20...(Other models you can see in the webshop)		

solenoid valves

solenoid valves (water)

MÜLLER

medium temperature: 90°C

duty cycle: 100%

			
1			
vm nr.	370003	Ref. No.	5001056
description	solenoid valve double angled 230VAC inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		
spare parts for	370003		
	vm nr.	370128	Ref. No. 5001057
solenoid valve body double angled inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V double-ways			
	vm nr.	371002	Ref. No. —
solenoid valve holder MÜLLER flange support			
	vm nr.	371009	Ref. No. 5001074
compression spring for solenoid coil			
	vm nr.	371011	Ref. No. —
spare parts kit membrane with long star star hight 8mm MÜLLER			
	vm nr.	371017	Ref. No. 5001066
solenoid coil MÜLLER 230VAC connection male faston 6.3mm			
	vm nr.	371122	Ref. No. —
solenoid valve filter ø 19mm H 10mm suitable for MÜLLER			
	vm nr.	501161	Ref. No. —
tap head for solenoid valve holder for solenoid coils			

accessories for	370003		
	vm nr.	371010	Ref. No. —
solenoid coil 230VAC connection with cable cable length 2000mm			
	vm nr.	371037	Ref. No. —
solenoid coil 24VAC 50/60Hz connection male faston 6.3mm			
	vm nr.	371038	Ref. No. —
solenoid coil 230VAC connection appliance plug			

			
1			
vm nr.	370001	Ref. No.	5001058
description	solenoid valve single angled 230VAC inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		
spare parts for	370001		
	vm nr.	370126	Ref. No. —
solenoid valve body single angled inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER plastic			
	vm nr.	371002	Ref. No. —
solenoid valve holder MÜLLER flange support			
	vm nr.	371009	Ref. No. 5001074
compression spring for solenoid coil			
	vm nr.	371011	Ref. No. —
spare parts kit membrane with long star star hight 8mm MÜLLER			
	vm nr.	371017	Ref. No. 5001066
solenoid coil MÜLLER 230VAC connection male faston 6.3mm			
	vm nr.	371122	Ref. No. —
solenoid valve filter ø 19mm H 10mm suitable for MÜLLER			
	vm nr.	501161	Ref. No. —
tap head for solenoid valve holder for solenoid coils			
accessories for	370001		
	vm nr.	371010	Ref. No. —
solenoid coil 230VAC connection with cable cable length 2000mm			
	vm nr.	371037	Ref. No. —
solenoid coil 24VAC 50/60Hz connection male faston 6.3mm			
	vm nr.	371038	Ref. No. —
solenoid coil 230VAC connection appliance plug			

			
vm nr.	370000	Ref. No.	5001062
description	solenoid valve triple angled 230VAC inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		
spare parts for	370000		
vm nr.	370130	Ref. No.	—
	solenoid valve body triple angled inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V triple-ways		
vm nr.	371002	Ref. No.	—
	solenoid valve holder MÜLLER flange support		
vm nr.	371009	Ref. No.	5001074
	compression spring for solenoid coil		
vm nr.	371011	Ref. No.	—
	spare parts kit membrane with long star star height 8mm MÜLLER		
vm nr.	371017	Ref. No.	5001066
	solenoid coil MÜLLER 230VAC connection male faston 6.3mm		
vm nr.	371122	Ref. No.	—
	solenoid valve filter ø 19mm H 10mm suitable for MÜLLER		
vm nr.	501161	Ref. No.	—
	tap head for solenoid valve holder for solenoid coils		
accessories for	370000		
vm nr.	371010	Ref. No.	—
	solenoid coil 230VAC connection with cable cable length 2000mm		
vm nr.	371037	Ref. No.	—
	solenoid coil 24VAC 50/60Hz connection male faston 6.3mm		
vm nr.	371038	Ref. No.	—
	solenoid coil 230VAC connection appliance plug		

spare parts and accessories

valve bodies

			
vm nr.	370128	Ref. No.	5001057
description	solenoid valve body double angled inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V double-ways		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

solenoid coils

			
vm nr.	371017	Ref. No.	5001066
description	solenoid coil MÜLLER 230VAC connection male faston 6.3mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

miscellaneous

			
vm nr.	371009	Ref. No.	5001074
description	compression spring for solenoid coil		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

ROBERTSHAW/INVENSYS

medium temperature: 90°C 90°C 60°C
ambient temperature: 60°C 25°C 60°C
duty cycle: 40% 100% 100%

			
vm nr.	372019	Ref. No.	5011050
description	solenoid valve double angled 230VAC inlet 3/4" outlet 11.5mm DN10 EATON (INVENSYS)		

solenoid valves with reducers

single

			
vm nr.	372005	Ref. No.	5056378
description	solenoid valve single straight 200-240VAC inlet 3/4" outlet 10.5 t.max. 90°C duty cycle 100% ROBERTSHAW S02810/00 plastic		

			
vm nr.	371145	Ref. No.	5001059
description	solenoid valve single straight 230VAC inlet 3/4" outlet 11.5mm input 12l/min		
For models:	OD10.10, OD10.20, OD12.20, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSG10.10, OSG12.20, OSG6.10		

2-fold			
			
vm nr.	374108	Ref. No.	5056379
description	solenoid valve double angled 230VAC inlet 3/4" outlet 10mm t.max. 90°C ROBERTSHAW plastic connection coded		

RPE			
			
vm nr.	374067	Ref. No.	5011013
description	solenoid valve single straight 230VAC inlet 3/8" outlet 3/8" input/output 10-20l/min t.max. 60°C RPE plastic flow regulating valve inlet white male faston 6.3mm		

solenoid valves with reducers			
single			
			
vm nr.	370744	Ref. No.	5011020 5030489
description	solenoid valve single straight 230VAC inlet 3/4" outlet 11mm input 10-20l/min t.max. 60°C RPE plastic flow regulating valve inlet white male faston 6.3mm		

TP			
			
vm nr.	370021	Ref. No.	5001080
description	solenoid valve double straight 230VAC inlet 3/4" outlet 11.5mm DN10 TP flow regulating valve inlet white		
spare parts for	370021		
vm nr.	371013	Ref. No.	—
solenoid coil TP 230VAC 50/60Hz			
accessories for	370021		
vm nr.	371220	Ref. No.	—
reducer TP flow rate 3l/min red tolerance ±15%			
vm nr.	371221	Ref. No.	—
reducer TP flow rate 5.5l/min yellow tolerance ±15%			
vm nr.	371222	Ref. No.	—
reducer TP flow rate 6l/min grey tolerance ±15%			
vm nr.	371223	Ref. No.	—
reducer TP flow rate 10l/min white tolerance ±15%			
vm nr.	371224	Ref. No.	—
reducer TP flow rate 12l/min bronze tolerance ±15%			
vm nr.	371225	Ref. No.	—
reducer TP flow rate 16l/min light brown tolerance ±15%			
vm nr.	371226	Ref. No.	—
reducer TP flow rate 20l/min red tolerance ±15%			
vm nr.	371230	Ref. No.	—
reducer TP flow rate 0.25l/min red tolerance ±25%			
vm nr.	371231	Ref. No.	—
reducer TP flow rate 0.35l/min violet tolerance ±25%			
vm nr.	371232	Ref. No.	—
reducer TP flow rate 0.5l/min orange tolerance ±25%			
vm nr.	371233	Ref. No.	—
reducer TP flow rate 0.8l/min white tolerance ±25%			
vm nr.	371234	Ref. No.	—
reducer TP flow rate 1l/min light blue tolerance ±25%			
vm nr.	371235	Ref. No.	—
reducer TP flow rate 1.2l/min brown tolerance ±25%			
vm nr.	371236	Ref. No.	—
reducer TP flow rate 1.5l/min light brown tolerance ±25%			

Table continues overleaf

accessories for 370021				
	vm nr.	371237	Ref. No.	—
reducer TP flow rate 2.5l/min yellow tolerance ±25%				
	vm nr.	371238	Ref. No.	—
reducer TP flow rate 3.4l/min dark green tolerance ±25%				
	vm nr.	371239	Ref. No.	—
reducer TP flow rate 5l/min black tolerance ±25%				
	vm nr.	371240	Ref. No.	—
reducer TP flow rate 8l/min blue tolerance ±20%				



componenti per elettrodomestici



1

vm nr.	370025	Ref. No.	5011000	
description solenoid valve triple straight 230VAC inlet 3/4" outlet 11.5mm DN10 TP				
For models: OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20				
spare parts for 370025				
 vm nr. 371013 Ref. No. — solenoid coil TP 230VAC 50/60Hz				
accessories for 370025				
 vm nr. 371220 Ref. No. — reducer TP flow rate 3l/min red tolerance ±15%				
 vm nr. 371221 Ref. No. — reducer TP flow rate 5.5l/min yellow tolerance ±15%				
 vm nr. 371222 Ref. No. — reducer TP flow rate 6l/min grey tolerance ±15%				
 vm nr. 371223 Ref. No. — reducer TP flow rate 10l/min white tolerance ±15%				
 vm nr. 371224 Ref. No. — reducer TP flow rate 12l/min bronze tolerance ±15%				
 vm nr. 371225 Ref. No. — reducer TP flow rate 16l/min light brown tolerance ±15%				
 vm nr. 371226 Ref. No. — reducer TP flow rate 20l/min red tolerance ±15%				
 vm nr. 371230 Ref. No. — reducer TP flow rate 0.25l/min red tolerance ±25%				
 vm nr. 371231 Ref. No. — reducer TP flow rate 0.35l/min violet tolerance ±25%				

accessories for 370025				
	vm nr.	371232	Ref. No.	—
reducer TP flow rate 0.5l/min orange tolerance ±25%				
	vm nr.	371233	Ref. No.	—
reducer TP flow rate 0.8l/min white tolerance ±25%				
	vm nr.	371234	Ref. No.	—
reducer TP flow rate 1l/min light blue tolerance ±25%				
	vm nr.	371235	Ref. No.	—
reducer TP flow rate 1.2l/min brown tolerance ±25%				
	vm nr.	371236	Ref. No.	—
reducer TP flow rate 1.5l/min light brown tolerance ±25%				
	vm nr.	371237	Ref. No.	—
reducer TP flow rate 2.5l/min yellow tolerance ±25%				
	vm nr.	371238	Ref. No.	—
reducer TP flow rate 3.4l/min dark green tolerance ±25%				
	vm nr.	371239	Ref. No.	—
reducer TP flow rate 5l/min black tolerance ±25%				
	vm nr.	371240	Ref. No.	—
reducer TP flow rate 8l/min blue tolerance ±20%				

pressure switches

for combi-steamers

1

vm nr.	541806	Ref. No.	5009061 5009063
description	pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"		
For models:	OD10.10, OD10.20, OD12.20, OD20.20, OD6.10, OES10.20, OES12.20, OES6.06, OSG10.10, OSG12.20, OSG20.20, OSG6.10		
accessories for	541806		
	vm nr.	541814	Ref. No. —
protection cap for pressure switch EPDM XP600			

			
1			
vm nr.	541779	Ref. No.	2619860 5013052
description	pressure control ø 45mm pressure range 0-120mbar for combi-steamer suitable for CONVOTHERM p max 4bar		

			
1			
vm nr.	542384	Ref. No.	2629926
description	pressure control ø 45mm pressure range 150mbar for combi-steamer CONVOTHERM CONVOClean p max 4bar		

			
1			
vm nr.	541833	Ref. No.	2619149 5013051
description	pressure control ø 45mm pressure range 200mbar for cleaning system connection 1/4" suitable for CONVOTHERM p max 4bar preset at 0.2bar pressure connection 1/4"		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

			
1			
vm nr.	541642	Ref. No.	2611026 2611504 5009055 5013050
description	pressure control ø 45mm pressure range 80mbar connection 12mm pressure connection 12mm		
For models:	OS10.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

electrodes

			
1			
vm nr.	400076	Ref. No.	5009062
description	level electrode 1/2" total length 190mm probe L 125/155mm insulated probe length 113mm connection bullet connector		
For models:	HUD6.10, OD10.10, OD10.20, OD6.10, OS10.10, OS6.10, OSC10.10, OSC20.10, OSC6.10, OSP10.10, OSP6.10		

			
1			
vm nr.	400075	Ref. No.	5009065
description	level electrode 1/2" total length 270mm probe L 185/235mm insulated probe length 113mm connection bullet connector		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OS10.20, OS12.20, OS20.10, OS20.20, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20		

			
1			
vm nr.	400216	Ref. No.	5009068
description	level electrode 1/8" probe L 130mm insulated probe length 114mm		
For models:	OD10.10, OD6.10		

			
1			
vm nr.	400217	Ref. No.	5009066
description	level electrode 1/8" probe L 161mm insulated probe length 114mm		
For models:	OD10.10, OD6.10		

			
1			
vm nr.	400218	Ref. No.	5009069
description	level electrode with thread probe L 190mm		

flow meters and flow sensors

flow sensors

			
1			
vm nr.	403753	Ref. No.	5056377
description	flow meter inlet ø 10 outlet ø 10 L 68mm		



fans

axial fans

ebm-papst



1

vm nr.	601121 ¹	Ref. No.	5008068
description	axial fan L 119mm W 119mm H 38mm 12VDC 4.5W bearing ball bearing manuf. no. 4182NX metal connection male faston 2.8mm ebm-papst fan wheel ø 110mm temp.-resist. 75°C		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

vm nr.	601121 ¹	Ref. No.	5008068
description	axial fan L 119mm W 119mm H 38mm 12VDC 4.5W bearing ball bearing manuf. no. 4182NX metal connection male faston 2.8mm ebm-papst fan wheel ø 110mm temp.-resist. 75°C		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

¹with ball bearings



1

vm nr.	601120 ¹	Ref. No.	5008065
description	axial fan L 92mm W 92mm H 25mm 12VDC 0.8W bearing ball bearing manuf. no. 3412 plastic connection cable 1600mm ebm-papst fan wheel ø 85mm temp.-resist. 75°C		
For models:	OD10.10, OD6.10		
accessories for	601120		
	vm nr.	691103	Ref. No.
	guard ø 90mm mounting distance 83mm for axial fan 92mm		

¹with ball bearings

import



1

vm nr.	601712 ¹	Ref. No.	5018023 5018040
description	axial fan L 120mm W 120mm H 38mm 12VDC 10W bearing ball bearing connection cable 320mm plastic ADDA fan wheel ø 110mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

¹with ball bearings



1

vm nr.	602154	Ref. No.	5056318
description	axial fan L 120mm W 120mm H 38mm 12VDC 6.7W bearing ball bearing manuf. no. PMD1212PMB3-A cable length 1500mm SUNON suitable for CONVOTHERM 4 fan wheel ø 110mm housing plastic		



1

vm nr.	601747 ¹	Ref. No.	2118786
description	axial fan L 92mm W 92mm H 25mm 12VDC 2.3W bearing ball bearing connection cable 300mm SUNON		
For models:	OES6.06		


¹with ball bearings

hot air motors



1

vm nr.	500931	Ref. No.	5008051 5008054 5008054K
description	fan motor 0.32kW		
For models:	OD12.20, OD20.10, OD20.20		


1

vm nr.	601719	Ref. No.	5008036 5008036K 5008049
description	fan motor 200-240/346-415V 200-254/346-480V 3 phase 50/60Hz 0.4/0.68kW 1420/1700rpm speeds 1 L1 152mm L2 44mm L3 54mm ø 125mm 1.2/2.1A at 50Hz 1420rpm at 60Hz 1720rpm type L9Cw4D2-450 D1 ø 15mm D2 ø 14mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	501576	Ref. No.	5056347
description	fan motor 215-320V 3 phase 50Hz 0.35kW 1430rpm L1 140mm L2 49mm L3 35mm 1.6-1.65A type HANNING no. V3A145-040P0035-015-0020S0-819 D1 ø 17mm D2 ø 12.5mm		
spare parts for	501576		
	vm nr.	694646	Ref. No. 2617295
 shaft sealing set for hot air motors			

1

vm nr.	601720	Ref. No.	2617286 5018019 5018021
description	fan motor 200-240/346-415V 200-254/346-480V 3 phase 50/60Hz 0.6kW 1380/1650rpm speeds 1 L1 151mm L2 47mm L3 37mm M10x1.5 2.8/1.6A power input 820W type L9Fw4D-605 D1 ø 17mm D2 ø 13.5mm set		
For models:	OEB10.10, OEB20.10, OEB6.10, OEB6.20, OES10.10, OES20.10, OES6.10, OES6.20, OGB10.10, OGB20.10, OGB6.10, OGB6.20, OGS10.10, OGS20.10, OGS6.10, OGS6.20		
spare parts for	601720		
	vm nr.	510686	Ref. No. 6005079
 gasket set for fan motor ID ø 15mm			



1

vm nr.	602138	Ref. No.	2625108 5018057
description	fan motor 230/400V 3 phase 50/60Hz 0.15kW 2740/3270rpm L1 85mm L2 58mm L3 12mm ø 123mm shaft flat length 23mm M5 0.8A type V3A120-025P0015-036-001OS0-841 D1 ø 8mm D2 ø 8x6mm with fixing kit HANNING for CONVOTHERM model OES mini mounting distance 100mm		



1

vm nr.	602027	Ref. No.	2618802
description	fan motor 230V 1 phase 50/60Hz 0.12kW 2800/3400rpm L1 86mm L2 56mm L3 10mm ø 135mm shaft flat length 20.8mm M5 0.8A suitable capacitor 5µF compact type V1A120-025P0012-036-001OS0-840 D1 ø 8mm D2 ø 4.9mm		
For models:	OES6.06		
spare parts for	602027		
	vm nr.	694800	Ref. No. 2618801
 engine shaft gasket ø 18mm hole ø 8mm Mini series Qty 1 pcs			



1

vm nr.	602147	Ref. No.	2617287 5018020 5018022
description	fan motor 200-240/346-415V 200-254/346-480V 3 phase 50/60Hz 1.15kW 1410/1700rpm speeds 1 L1 200mm L2 60mm L3 38mm M10 IT 4.0/2.3A at 50Hz 200-240/346-415V at 60Hz 200-254/346-480V at 50Hz 1410rpm at 60Hz 1700rpm type L9FGw4D-607 D1 ø 17mm D2 ø 13.5mm combi-steamer CONVOTHERM series P3 model 10.20/12.20/20.20 with mounting accessories mounting distance 177mm mounting ø 9mm		



1

vm nr.	601733	Ref. No.	5008060 5008060K
description	fan motor 380-415/380-480V 3 phase 50/60Hz 0.4/0.68kW 1420/1720rpm L1 155mm L2 45mm L3 55mm 0.55/1.1A at 50Hz 380-415V at 60Hz 380-480V at 50Hz 940-1420rpm at 60Hz 1120-1720rpm type L9zAw64D-449 D1 ø 15mm D2 ø 14mm kit		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	605169	Ref. No.	2617285 5018003
description	fan motor 380-415/380-480V 3 phase 50/60Hz 0.9kW 700/1380rpm speeds 2 L1 205mm L2 30mm L3 65mm 0.9/2.1A D1 ø 17mm D2 ø 13.5mm		
For models:	OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, OGB10.20, OGB12.20, OGB20.20, OGS10.20, OGS12.20, OGS20.20		
spare parts for	605169		
	vm nr.	694646	Ref. No. 2617295
	shaft sealing set for hot air motors		



1

vm nr.	601872	Ref. No.	2618803
description	fan wheel D1 ø 200mm H1 43mm blades 45 D2 ø 8.3mm D3 ø 8.3mm H2 25mm		
For models:	OES6.06		



1

vm nr.	514426	Ref. No.	6010001
description	fan wheel D1 ø 350mm H1 110mm blades 12 D2 ø 16.8mm D3 ø 13.2mm H2 15mm H3 75mm		
For models:	OEB10.10, OEB20.10, OEB6.10, OEB6.20, OES10.10, OES20.10, OES6.10, OES6.20, OGB10.10, OGB20.10, OGB6.20, OGS10.10, OGS20.10, OGS6.20		



1

vm nr.	601873	Ref. No.	2619959 6010003
description	fan wheel D1 ø 405mm H1 150mm blades 12 D2 ø 14mm D3 ø 17mm H2 22mm		
For models:	OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, OGB10.20, OGB12.20, OGB20.20, OGS10.20, OGS12.20, OGS20.20		



1

vm nr.	514439	Ref. No.	6015034
description	gasket graphite ED ø 82.5mm ID ø 52.5mm thickness 2mm		
For models:	OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	510686	Ref. No.	6005079
description	gasket set for fan motor ID ø 15mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		



1

vm nr.	402888	Ref. No.	2617283 5018002
description	motor three phase current 0.6kW 380-415V 50/60Hz 3 phase 0.6-1.6A shaft ø 17mm shaft length 88mm 710-1390 / 820-1690rpm type L9yzw84D-584 HANNING		
For models:	OEB10.10, OEB20.10, OEB6.10, OEB6.20, OES10.10, OES20.10, OES6.10, OES6.20, OGB10.10, OGB20.10, OGB6.10, OGB6.20, OGS10.10, OGS20.10, OGS6.10, OGS6.20		



1

vm nr.	694646	Ref. No.	2617295
description	shaft sealing set for hot air motors		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

hot air fans

accessories


miscellaneous



1


vm nr.	694800	Ref. No.	2618801
description	engine shaft gasket ø 18mm hole ø 8mm Mini series Qty 1 pcs		
For models:	OES6.06		

radial fans

1

vm nr.	601181	Ref. No.	5018000
description	radial fan 230V voltage AC 50Hz 100W H1 170mm L1 175mm D1 ø 50mm W1 115mm W2 40mm H2 45mm		
For models:	OGB10.10, OGB12.20, OGB20.10, OGB6.10, OGB6.20, OGS10.10, OGS12.20, OGS20.10, OGS6.10, OGS6.20		

1

vm nr.	601742	Ref. No.	5018001
description	radial fan 230V voltage AC 50Hz 140W H1 190mm L1 190mm D1 ø 50mm W1 133mm W2 28mm H2 55mm W3 83mm H3 83mm		
For models:	OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGS10.20, OGS12.20, OGS20.10, OGS20.20		

accessories universal



1

vm nr.	802191	Ref. No.	7015200
description	puller for fan wheel seat ø 28/34mm thread M16x1.5 WS 17		



motors

accessories



vm nr.	696344	Ref. No.	5008067
description	gasket set for three-phase motor		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

pumps

wash and rinse pumps

HANNING

pumps



vm nr.	501563	Ref. No.	5056337
description	pump inlet ø 24 outlet ø 24 type UP30-494 200-240V 50/60Hz 1 phase 0.1kW L 146mm capacitor 2.5µF HANNING hose clamps		

drain pumps

HANNING



vm nr.	501569	Ref. No.	5056380
description	drain pump 38/43W 200-240V inlet ø 24mm outlet ø 24mm 50/60Hz HANNING type DPS25R-393 type series Haflowtic compact		

vibration pumps



vm nr.	500580	Ref. No.	5008011 5008011K 5030635
description	vibration pump 230V 60W 50/60Hz inlet ø 7 outlet ø 1/8" IT CEME type E512 with accessories duty cycle 1/2 ambient temperature max. 60°C medium temp max. 35°C overheating protection 110°C CleanJet		



vm nr.	499142	Ref. No.	5018028 5018035
description	vibration pump type CP06.728.0 220/240V 70W 60Hz inlet ø 6 outlet ø 6 with thermal fuse L 130mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



vm nr.	501547	Ref. No.	5056376
description	vibration pump type MPP2.02.041.2/ST/S 208-240V 14W 50Hz inlet ø 6.5 outlet ø 7.5 ARS L 87mm		

condensators & interference suppression filters

filters

interference suppression filters



vm nr.	365218	Ref. No.	4001078
description	interference suppression filter type RC-01 capacity 0.15µF L 37.5mm H 37mm W 10mm 4700hm		

line filters

with housing



1

vm nr.	365222	Ref. No.	5056974
description	line filter type 5500.2218 250V 50/60Hz conductor 2 with E connection F6.3x0.8 L 65mm H 42mm W 50mm screw aluminium		

RC circuits



1

vm nr.	380272	Ref. No.	4001077
description	RC circuit for contactors type 910-304-585-50 130-250V 50-60Hz conductor 2 connection cable plastic Qty 1 pcs for contactors LS4_LS15K type AEG LR2K A250 type GE BS2R2R		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		



1

vm nr.	381483	Ref. No.	5056977
description	RC circuit for CONVOTHERM type MT151415 1200hm capacity 0.15µF		



1

vm nr.	381482	Ref. No.	5056980
description	RC circuit for CONVOTHERM type MT151417 1500hm capacity 0.47µF		



1

vm nr.	381478	Ref. No.	5056981
description	RC circuit for CONVOTHERM type MT151418 1500hm capacity 0.47µF		



1

vm nr.	381479	Ref. No.	5056979
description	RC circuit type SAWI 610303 1500hm capacity 0.47µF		

fuses

fine fuses



1

vm nr.	358600	Ref. No.	4005064
description	fine fuse size ø5x20mm 1A slow-acting rated 250V Qty 10 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20... (Other models you can see in the webshop)		



1

vm nr.	358603	Ref. No.	4005066 4056944
description	fine fuse size ø5x20mm 2A slow-acting rated 250V Qty 10 pcs		
For models:	AR108, AR12, AR18, AR28, AR40, AR54, AR72, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20... (Other models you can see in the webshop)		



1

vm nr.	358605	Ref. No.	4056945
description	fine fuse size ø5x20mm 3.15A slow-acting rated 250V Qty 10 pcs		



1

vm nr.	358607	Ref. No.	4005068
description	fine fuse size ø5x20mm 6.3A slow-acting rated 250V Qty 10 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		



1

vm nr.	358751	Ref. No.	4005069
description	fine fuse size ø6.3x32mm 6.3A fast-acting rated 500V Qty 10 pcs		

slow-acting



1

vm nr.	358188	Ref. No.	4056355
description	fine fuse size ø6.3x32mm 10A slow-acting rated 500V Qty 10 pcs		



1

vm nr.	358189	Ref. No.	4056354
description	fine fuse size ø6.3x32mm 4A slow-acting rated 500V Qty 10 pcs		

fine fuse holders



1

vm nr.	550105	Ref. No.	4004010
description	rail-mounted terminal WIELAND type WK10/SIU 5X20 /V0 suitable fuse ø5x20mm 1.0-16mm ² 10A rated 250V		
For models:	AR108, AR12, AR18, AR28, AR40, AR54, AR72, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

screw locks

D0-system (NEOZED)



1

vm nr.	358073	Ref. No.	4005053
description	fuse size D01 10A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		



1

vm nr.	358043	Ref. No.	4005054
description	fuse size D01 16A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	HUD12.20, HUD20.10		



1

vm nr.	358070	Ref. No.	4005050
description	fuse size D01 2A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	AR100, AR108, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		



1

vm nr.	358071	Ref. No.	4005051
description	fuse size D01 4A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	AR100, AR108, AR30, AR40, AR50, AR54, AR72, OES12.20, UG10.10, UG20.10, UG6.10		



1

vm nr.	358072	Ref. No.	4005052
description	fuse size D01 6A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	OEB20.20, UG20.20		



1

vm nr.	358048	Ref. No.	4005058
description	fuse size D02 20A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	AR108, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10		



1

vm nr.	358044	Ref. No.	4005046 4005055
description	fuse size D02 25A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	AR100, AR108, HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, UG10.20		

			
1			
vm nr.	358045	Ref. No.	2212003 4005056
description	fuse size D02 35A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	HUD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OES20.10, UG20.10, UG20.20		

			
1			
vm nr.	358046	Ref. No.	4005057
description	fuse size D02 50A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20		

			
1			
vm nr.	358047	Ref. No.	4005059
description	fuse size D02 63A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	OEB20.10, OES20.10		

gauge pieces (NEOZED)

			
1			
vm nr.	358055	Ref. No.	4005013
description	gauge piece size D01 suitable for 10A		

			
1			
vm nr.	358052	Ref. No.	4005010
description	gauge piece size D01 suitable for 2A		
For models:	AR100, AR108, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		

			
1			
vm nr.	358053	Ref. No.	4005011
description	gauge piece size D01 suitable for 4A		
For models:	AR100, AR108, AR30, AR40, AR50, AR54, AR72, OES12.20, OES20.20, UG10.10, UG20.10, UG6.10		

			
1			
vm nr.	358054	Ref. No.	4005012
description	gauge piece size D01 suitable for 6A		
For models:	UG20.20		

			
1			
vm nr.	358064	Ref. No.	4005021
description	gauge piece size D02 suitable for 16A		
For models:	OD10.20, OD12.20, OD20.10, OSP10.20, OSP12.20		

			
1			
vm nr.	358065	Ref. No.	4005014
description	gauge piece size D02 suitable for 20A		
For models:	AR108, HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
1			
vm nr.	358066	Ref. No.	4005015
description	gauge piece size D02 suitable for 25A		
For models:	AR100, AR108, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20, UG10.20		

			
1			
vm nr.	358067	Ref. No.	4005016
description	gauge piece size D02 suitable for 35A		
For models:	HUD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OES20.10, OSC20.20, OSP20.20, UG20.10, UG20.20		

			
1			
vm nr.	358068	Ref. No.	4005017
description	gauge piece size D02 suitable for 50A		
For models:	OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20		

fuse holders

			
1			
vm nr.	358057	Ref. No.	4004020
description	fuse holder suitable fuse D01 1-pole-pole 16A rated 400V		
For models:	AR100, AR108, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, HUD12.20, HUD20.10, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		

			
1			
vm nr.	358059	Ref. No.	4004030
description	fuse holder suitable fuse D01 ø 24mm mounting ø 14mm 1-pole-pole 16A rated 400V L 30mm		
For models:	AR100, AR108, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, HUD12.20, HUD20.10, HUD20.20, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		

			
1			
vm nr.	358058	Ref. No.	4004023 4004025
description	fuse holder suitable fuse D02 1-pole-pole 63A rated 400V		
For models:	AR108, HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OES10.20, OES12.20, OES20.10, OES20.20, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10, UG10.20, UG20.10, UG20.20		

			
1			
vm nr.	358061	Ref. No.	4004035
description	fuse holder suitable fuse D02 ø 25mm mounting ø 18mm rated 400V L 30mm		
For models:	AR100, AR108, HUD12.20, HUD20.10, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OES10.20, OES12.20, OES20.10, OES20.20, UG10.20, UG20.10, UG20.20		

line circuit breakers

SCHNEIDER ELECTRIC

			
1			
vm nr.	381457	Ref. No.	5056830
description	line circuit breaker 1-pole tripping type B 63A rated 230/400V connection screw auxiliary contacts 1NO mounting rail		

electric accessories

cables

connection cables

			
1			
vm nr.	579000	Ref. No.	5009304
description	connection cable L 1900mm 9-pole suitable for CONVOTHERM connection plug plug type RS232 interface		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
1			
vm nr.	579006	Ref. No.	5056357
description	data cable L 1020mm 8-pole for combi-steamer suitable for CONVOTHERM plug type RJ45		

terminals

PCB terminal blocks

			
1			
vm nr.	551367	Ref. No.	5012003
description	PCB terminal block 12-pole raster size 3.5mm		

			
1			
vm nr.	551369	Ref. No.	5002091
description	PCB terminal block 12-pole raster size 3.5mm flat		

			
1			
vm nr.	550810	Ref. No.	4006003
description	PCB terminal block 12-pole raster size 5mm		

			
1			
vm nr.	551360	Ref. No.	5002097
description	PCB terminal block 16-pole raster size 3.5mm		

			
1			
vm nr.	550802	Ref. No.	4005093
description	PCB terminal block 4-pole raster size 5mm		

			
1			
vm nr.	551338	Ref. No.	4006022
description	PCB terminal block 6-pole cross section 1.5mm²		

			
1			
vm nr.	551363	Ref. No.	4006021
description	PCB terminal block 7-pole raster size 7mm cross section 1.5mm²		

			
1			
vm nr.	551370	Ref. No.	5002096
description	PCB terminal block 8-pole raster size 3.5mm flat		

			
1			
vm nr.	551364	Ref. No.	5012002
description	PCB terminal block 8-pole raster size 5mm		

			
1			
vm nr.	551365	Ref. No.	5002095
description	PCB terminal block 9-pole raster size 3.5mm		

			
1			
vm nr.	551368	Ref. No.	5002098
description	PCB terminal block 9-pole raster size 3.5mm		

			
1			
vm nr.	551361	Ref. No.	5002090
description	PCB terminal block 9-pole raster size 5mm		

rail-mounted terminals

WIELAND

rail-mounted terminals type 9700A

			
1			
vm nr.	550373	Ref. No.	4006040
description	rail-mounted terminal WIELAND type 9700A/10 S35 1.5-16mm² top-hat rail 35mm grey W 10mm L 49mm		
For models:	AR108, HUD12.20, HUD20.20, OD10.10, OD6.10, OSC10.10, OSP10.10, OSP6.10		

			
1			
vm nr.	550382	Ref. No.	4006050
description	rail-mounted terminal WIELAND type 9700A/12 S35 2.5-25mm² top-hat rail 35mm grey W 12mm L 59mm		
For models:	HUD20.10, OD10.20, OD12.20, OD20.10, OSC10.20, OSC12.20, OSC20.10, OSP10.20, OSP12.20, OSP20.10, OSP6.10		



1

vm nr.	550376	Ref. No.	4006055
description	rail-mounted terminal WIELAND type 9700A/16 S35 2.5-35mm² top-hat rail 35mm grey W 16mm L 59mm		
For models:	HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20		



1

vm nr.	550378	Ref. No.	4006058
description	rail-mounted terminal WIELAND type 9700A/16 SL2 S35 2.5-35mm² top-hat rail 35mm yellow/green W 16mm L 53mm		
For models:	HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	550371	Ref. No.	4006023
description	rail-mounted terminal WIELAND type 9700A/6 S35 0.5-4mm² top-hat rail 35mm grey W 6mm L 46.6mm		
For models:	AR18, AR28, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSC10.10, OSC20.10, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	550372	Ref. No.	4006026
description	rail-mounted terminal WIELAND type 9700A/6 SL2 S35 0.5-4mm² top-hat rail 35mm yellow/green W 6mm L 48.5mm		
For models:	AR108, AR18, AR28, AR40, AR54, AR72, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	550383	Ref. No.	4006033
description	rail-mounted terminal WIELAND type 9700A/8 S35 1.0-10mm² top-hat rail 35mm blue W 8mm L 46.6mm		
For models:	AR40, AR54, AR72, HUD10.10, OD10.10, OD10.20, OD12.20, OD6.10, OSC10.10, OSC6.10, OSP10.10, OSP6.10		



1

vm nr.	550381	Ref. No.	4006030
description	rail-mounted terminal WIELAND type 9700A/8 S35 1.0-10mm² top-hat rail 35mm grey W 8mm L 46.6mm		
For models:	AR40, AR54, AR72, HUD10.10, HUD20.10, HUD20.20, OD10.10, OD6.10, OSC10.10, OSC6.10, OSP10.10, OSP6.10		

installation terminals




1

vm nr.	550400 ¹	Ref. No.	4006043
description	installation terminal WIELAND type WK4/D2/2U/V0 0.5-6mm² TS35+TS32 grey DUO		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

¹duo-modular terminal

fuse terminal blocks



1

vm nr.	550105	Ref. No.	4004010
description	rail-mounted terminal WIELAND type WK10/SIU 5X20 /V0 suitable fuse ø5x20mm 1.0-16mm² 10A rated 250V		
For models:	AR108, AR12, AR18, AR28, AR40, AR54, AR72, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

accessories


1

vm nr.	550410	Ref. No.	4006045
description	end barrier for duo-modular terminal clamps up to 4mm ² grey		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10		



1

vm nr.	550337	Ref. No.	4004011
description	end barrier for fuse terminal clamps up to 4mm ²		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD6.10		



1

vm nr.	550392	Ref. No.	4006051
description	end barrier for rail-mounted terminal clamps up to 25/35mm ² blue		
For models:	HUD20.10, HUD20.20		



1

vm nr.	550384	Ref. No.	4006024
description	end barrier for rail-mounted terminal clamps up to 4mm ² blue		
For models:	HUD6.10		



1

vm nr.	550394	Ref. No.	4006032
description	isolation barrier for rail-mounted terminal clamps up to 10mm ² blue		
For models:	HUD10.10, HUD20.10		



1

vm nr.	550395	Ref. No.	4006042
description	isolation barrier for rail-mounted terminal clamps up to 16mm ² yellow/green		
For models:	HUD12.20, HUD20.20		



1

vm nr.	550393	Ref. No.	4006025
description	isolation barrier for rail-mounted terminal clamps up to 4mm ² grey		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10		

miscellaneous



1

vm nr.	551421	Ref. No.	4056408
description	rail-mounted terminal PHOENIX CONTACT type ST 10-TWIN 0.2-16mm ² grey W 10.2mm L 95.7mm max. 57A max 1000V for combi-steamer cross section 10mm ²		




1

vm nr.	551427	Ref. No.	4056402
description	rail-mounted terminal PHOENIX CONTACT type ST 16-TWIN 0.2-25mm ² grey W 12.2mm L 108mm max. 76A max 1000V for combi-steamer cross section 16mm ²		




1

vm nr.	551410	Ref. No.	4056990
description	rail-mounted terminal PHOENIX CONTACT type ST 4 4mm ² blue W 6mm L 56mm max. 30A max 800V		



1

vm nr.	551403	Ref. No.	4056405
description	rail-mounted terminal PHOENIX CONTACT type ST 4 4mm ² grey W 6.2mm L 56mm		




1

vm nr.	551412	Ref. No.	4056404
description	rail-mounted terminal PHOENIX CONTACT type ST 4-PE 4mm ² green/yellow W 35mm L 56mm for combi-steamer CONVOTHERM		



1

vm nr.	551419	Ref. No.	4056985
description	rail-mounted terminal PHOENIX CONTACT type ST2,5-QUATTRO-PE 0.08-4mm ² yellow/green W 5.2mm L 72.5mm for combi-steamer cross section 2.5mm ²		



1

vm nr.	551418	Ref. No.	4056987
description	rail-mounted terminal PHOENIX CONTACT type ST2,5-QUATTRO 0.08-4mm ² blue W 5.2mm L 89.5mm max. 28A max 800V for combi-steamer cross section 2.5mm ²		



1

vm nr.	551424	Ref. No.	4056988
description	rail-mounted terminal PHOENIX CONTACT type ST2,5-QUATTRO 0.08-4mm ² grey W 5.2mm L 72mm max. 24A max 800V for combi-steamer cross section 2.5mm ²		



1

vm nr.	551392	Ref. No.	4056389
description	rail-mounted terminal PHOENIX CONTACT type ST4-HESI 4mm ² black W 6.2mm L 76.5mm max. 10A max 400V for combi-steamer 6.3x32		



1

vm nr.	551429	Ref. No.	4056390
description	rail-mounted terminal PHOENIX CONTACT type ST4-QUATTRO-PE 0.08-6mm ² yellow/green W 6.2mm L 82mm for combi-steamer cross section 4mm ²		




1

vm nr.	551417	Ref. No.	4056400
description	rail-mounted terminal PHOENIX CONTACT type ST6 0.2-10mm ² blue W 8.2mm L 69.5mm max. 50A max 1000V for combi-steamer		



1

vm nr.	551416	Ref. No.	4056398
description	rail-mounted terminal PHOENIX CONTACT type ST6 0.2-10mm ² grey W 8.2mm L 70mm max. 52A max 1000V for combi-steamer cross section 6mm ²		



1

vm nr.	551414	Ref. No.	4056399
description	rail-mounted terminal PHOENIX CONTACT type ST6-PE 0.2-10mm ² green/yellow W 8.2mm L 69.5mm		



1

vm nr.	551430	Ref. No.	4056834
description	rail-mounted terminal PHOENIX CONTACT type ST6-TWIN 0.2-10mm ² grey W 8.2mm L 90.5mm max. 52A max 1000V for combi-steamer cross section 6mm ²		


			
1			
vm nr.	551406	Ref. No.	4056411
description	rail-mounted terminal PHOENIX CONTACT type STU10/4x2.5 0.5-16mm ² grey W 10.3mm L 68mm max. 57A max 800V for combi-steamer cross section 10mm ²		

			
1			
vm nr.	551405	Ref. No.	4056410
description	rail-mounted terminal PHOENIX CONTACT type STU35/4x10 1.5-50mm ² grey W 16.2mm L 86mm max. 125A max 1000V for combi-steamer cross section 35mm ²		

			
1			
vm nr.	551423	Ref. No.	4056397
description	rail-mounted terminal PHOENIX CONTACT type UKH50 16-70mm ² blue W 20mm L 70.5mm max. 150A max 1000V for combi-steamer cross section 50mm ²		

			
1			
vm nr.	551415	Ref. No.	4056395
description	rail-mounted terminal PHOENIX CONTACT type UKH50 16-70mm ² grey W 20mm L 76mm max. 150A max 1000V for combi-steamer cross section 50mm ²		

			
1			
vm nr.	551413	Ref. No.	4056989
description	rail-mounted terminal PHOENIX CONTACT type UKH95 25-95mm ² grey W 25mm L 83mm max. 232A max 1000V for combi-steamer		

			
1			
vm nr.	551425	Ref. No.	4056833
description	rail-mounted terminal PHOENIX CONTACT type USLKG 95 25-95mm ² yellow/green W 25mm L 83mm for combi-steamer cross section 95mm ²		

			
1			
vm nr.	551426	Ref. No.	4056396
description	rail-mounted terminal PHOENIX CONTACT type USLKG50 16-50mm ² yellow/green W 20mm L 70.5mm for combi-steamer cross section 50mm ²		

			
1			
vm nr.	551408	Ref. No.	4056394
description	rail-mounted terminal PHOENIX CONTACT type UT 35 1.5-50mm ² blue W 16mm L 59mm max. 150A max 1000V for combi-steamer cross section 35mm ²		

			
1			
vm nr.	551404	Ref. No.	4056392
description	rail-mounted terminal PHOENIX CONTACT type UT 35 1.5-50mm ² grey W 16mm L 60mm max. 150A max 1000V for combi-steamer cross section 35mm ²		

			
1			
vm nr.	551409	Ref. No.	4056393
description	rail-mounted terminal PHOENIX CONTACT type UT 35-PE 1.5-35mm ² green/yellow W 16mm L 63mm max. 125A for combi-steamer		



1

vm nr.	551428	Ref. No.	4056831
description	terminal PHOENIX CONTACT type UHV95 35-95mm ² grey W 40mm L 110mm max. 232A max 1000V for combi-steamer		

accessories universal

terminal block end brackets



1

vm nr.	551389	Ref. No.	4056403
description	isolation barrier for rail-mounted terminal L 108mm W 2.2mm H 44mm PHOENIX CONTACT D-ST 16-TWIN		



1

vm nr.	551385	Ref. No.	4056412
description	isolation barrier for rail-mounted terminal L 68mm W 2.2mm H 40.7mm PHOENIX CONTACT D-STU 10		



1

vm nr.	551387	Ref. No.	4056986
description	isolation barrier for rail-mounted terminal L 72mm W 2.2mm H 29mm PHOENIX CONTACT D-ST 2.5-QUATTRO		



1

vm nr.	551393	Ref. No.	4056835
description	isolation barrier for rail-mounted terminal L 90.5mm W 2.2mm H 36mm PHOENIX CONTACT D-ST6 TWIN		



1

vm nr.	551390	Ref. No.	4056409
description	isolation barrier for rail-mounted terminal L 95.5mm W 2.2mm H 42.5mm PHOENIX CONTACT D-ST 10-TWIN		

electronic components

software

service sets



1

vm nr.	403078	Ref. No.	5019011
description	software suitable for CONVOTHERM Update-Box P3		

gas valves and ignition boxes

gas control valves

DUNGS



1

vm nr.	106909	Ref. No.	2625175 6006191
description	gas valve 230V 50/60Hz gas inlet 1/2" gas outlet 1/2" total length 105mm DUNGS type GB-LEP 055 D01 S42		
For models:	OD10.10, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		



HONEYWELL



1

vm nr.	107873	Ref. No.	6056952
description	gas valve type VE420AA1001 230V 50Hz gas inlet 3/4" gas outlet 3/4" pressure range 17-23mbar max 200mbar HONEYWELL suitable for CONVOTHERM 4		



1

vm nr.	107841	Ref. No.	6056955
description	gas valve type VK4115V 220-240V 50/60Hz gas inlet flange 32x32mm gas outlet flange 32x32mm thermocouple connection pilot connection pressure range 15-60mbar max 60mbar HONEYWELL hole distance 24mm M5 flange flange 32x32mm		
accessories for	107841		
	vm nr.	102845	Ref. No. —
	vm nr.	102846	Ref. No. —



1

vm nr.	106012	Ref. No.	6016010
description	gas valve type VK4115V 220-240V 50/60Hz gas inlet flange 32x32mm gas outlet flange 32x32mm thermocouple connection pilot connection pressure range 15-60mbar max 60mbar operator type HONEYWELL flange 32x32mm		
For models:	OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		
accessories for	106012		
	vm nr.	102845	Ref. No. —
	vm nr.	102846	Ref. No. —

SIT

ELETTROSIT



1

vm nr.	101993	Ref. No.	5001051
description	gas valve SIT type ELETTROSIT 230V gas inlet 1/2" gas outlet 1/2" thermocouple connection M9x1 pilot connection M10x1 lateral equiv. no. 0.810.126		
For models:	OD10.20, OD12.20		
spare parts for	101993		
	vm nr.	101312	Ref. No. 5001050
	vm nr.	101352	Ref. No. —
accessories for	101993		
	vm nr.	100006	Ref. No. —
	vm nr.	100904	Ref. No. —
	vm nr.	100905	Ref. No. —
	vm nr.	101301	Ref. No. —
	vm nr.	101303	Ref. No. —
	vm nr.	101309	Ref. No. —
	vm nr.	103104	Ref. No. —
	vm nr.	541504	Ref. No. —

ignition boxes

DUNGS



1

vm nr.	103102	Ref. No.	6006190
description	ignition box type DGAI.73 model 10.5.0TCL electrodes 2 starting time <10s waiting time >3s safety time <5s 230V 50/60Hz ignition cable male faston 2.8mm DUNGS protection IP20		
For models:	OD10.10, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

HONEYWELL



1

vm nr.	106606	Ref. No.	6016021
description	ignition box HONEYWELL type S4575B 1025 electrodes 3 waiting times safety time 5s 230-240V 4VA 50/60Hz		



1

vm nr.	106755	Ref. No.	6016020 6016022
description	ignition box HONEYWELL type S4575B 1066 electrodes 3 waiting times safety time 5s 230-240V 4VA 50/60Hz		
For models:	OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	107860	Ref. No.	6056957
description	ignition box HONEYWELL type S4965V3075 electrodes 1 safety time 5s 230V 2.5VA 50Hz		

ignition parts

pilot burners

SIT

100 series



1

vm nr.	106727	Ref. No.	5001088 6006160
description	pilot burner SIT type 100 series 3 flames LPG nozzle ø 0.35mm gas connection 6mm incl. 1x nozzle 0.25 LPG		
For models:	OD10.20, OD12.20		

accessories

pilot burner bottom parts



1

vm nr.	107700	Ref. No.	6006101
description	pilot burner bottom part SIT 100 series nozzle ø 0.25mm		
For models:	OD10.20, OD12.20		
spare parts for	107700		
	vm nr.	100916	Ref. No. —
compression spring for pilot burner Qty 1 pcs			
	vm nr.	100917	Ref. No. —
gasket for pilot burner Qty 1 pcs aluminium			
	vm nr.	100918	Ref. No. —
screw for pilot burner			
	vm nr.	102742	Ref. No. —
pilot burner nozzle LPG code 25 bore ø 0.25mm Qty 1 pcs			
accessories for	107700		
	vm nr.	100245	Ref. No. —
pilot burner nozzle LPG code 20 bore ø 0.2mm Qty 1 pcs thread M8x0.75			
	vm nr.	100246	Ref. No. —
pilot burner nozzle natural gas bore ø 0.35mm Qty 1 pcs thread M8x0.75			
	vm nr.	100904	Ref. No. —
locking screw M10x1 for pipe ø 4mm Qty 1 pcs			
	vm nr.	100905	Ref. No. —
locking screw M10x1 for pipe ø 6mm Qty 1 pcs			
	vm nr.	102110	Ref. No. —
pilot tube copper pipe ø 4mm thickness 1mm L 3000mm			

Table continues overleaf



accessories for		107700	
vm nr.	102111	Ref. No.	—
pilot tube copper pipe ø 6mm thickness 1mm L 3000mm			

pilot burner nozzles


1			
vm nr.	102972	Ref. No.	6005182
description	pilot burner nozzle natural gas code 40 bore ø 0.4mm Qty 1 pcs		

electrodes


1			
vm nr.	102476	Ref. No.	2617322 4018001 C4018001
description	glow plug conversion kit flange length 41mm flange width 20mm ø 11mm mounting distance 29mm cable length 60mm connection male faston 2.8mm total length 101mm L1 73mm L2 28mm 24V		
For models:	OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGS10.20, OGS12.20, OGS20.10, OGS20.20		


1			
vm nr.	102477	Ref. No.	2617321 4018002
description	glow plug conversion kit flange length 41mm flange width 20mm ø 11mm mounting distance 29mm cable length 60mm connection male faston 2.8mm total length 64mm L1 54mm L2 10mm 24V		
For models:	OGB10.10, OGB20.10, OGB6.10, OGB6.20, OGS10.10, OGS20.10, OGS6.10, OGS6.20		

1			
vm nr.	106517	Ref. No.	4008101
description	ignition electrode D1 ø 7mm D2 ø 8mm connection M4 L1 13mm BL1 18mm BL2 3mm BL3 23mm		
For models:	OD10.10, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

1			
vm nr.	107839	Ref. No.	4056951
description	ignition electrode flange length 38mm flange width 16mm D1 ø 9.5mm L1 36.5mm BL1 30mm connection 2.8x0.8 cable length 400mm fixing dimensions 4.5mm mounting distance 28mm with mounting accessories		

1			
vm nr.	107844	Ref. No.	4056950
description	ignition electrode set flange length 38mm flange width 17mm D1 ø 7mm L1 22mm L2 96mm BL1 62mm connection 2.8x0.8 cable length 400mm mounting distance 28mm M4 with mounting accessories CONVOTHERM model C4 Serie		

1			
vm nr.	106516	Ref. No.	4008104
description	monitoring electrode D1 ø 7mm D2 ø 8mm connection M4 L1 19mm BL1 18mm BL2 3mm BL3 22mm		
For models:	OD10.10, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		



vm nr.	109183 ¹	Ref. No.	2617320 4018000 c4018000
description	monitoring electrode flange length 38mm D1 9.5mm flange width 16mm L1 42mm BL1 28mm BL2 23mm connection F6.3x0.8 cable length 600mm with gasket and shrink tube		
For models:	OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

¹with gasket and shrink tube

ignition cables

pre-assembled cables



vm nr.	106514	Ref. No.	4008103
description	connecting cable for monitoring electrode cable length 1200mm connection F6.3/ø6mm		
For models:	OD10.10, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		



vm nr.	106515	Ref. No.	4008100
description	ignition cable cable length 1200mm connection F2.8/ø6mm		
For models:	OD10.10, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

thermocouples

accessories

miscellaneous



vm nr.	519625	Ref. No.	6056351
description	gasket for thermocouple ø 15mm ID ø 5mm H 1mm graphite suitable for combi-steamer series CONVOTHERM 4 Qty 5 pcs		

gas burners

forced air burners



vm nr.	107842	Ref. No.	2010014
description	burner L 150mm ø 50mm 20kW combi-steamer		



vm nr.	107840	Ref. No.	2010015
description	burner L 210mm ø 63mm 40kW combi-steamer CONVOTHERM series P3		

accessories

gaskets



vm nr.	112834	Ref. No.	6064078
description	gasket for burner chamber ø 140mm thickness 2mm graphite for combi-steamer suitable for CONVOTHERM 4 series 6.10/6.20/10.10		

gas nozzles

main nozzles

gas nozzles M10x1



vm nr.	106405	Ref. No.	6005177
description	gas injector thread M10x1 bore ø 2mm L 30mm WS 12		

pilot burner nozzles

pilot burner nozzles SIT

100 series



vm nr.	102972	Ref. No.	6005182
description	pilot burner nozzle natural gas code 40 bore ø 0.4mm Qty 1 pcs		



			
1			
vm nr.	107171	Ref. No.	6006008
description	pilot burner nozzle SIT natural/liquid gas bore ø 0.25mm Qty 1 pcs		

auxiliary gas parts

consumables

PTFE tapes

			
1			
vm nr.	890100	Ref. No.	7004052
description	PTFE tape reel L 12m W 12mm -200 up to +260°C approval DIN-DVGW, KTW temperature-resistant, elastic for fine thread thickness 0.1mm		
description	PTFE thread sealing tape for fine metal threads Application: All sanitary and heating circuits in hot and cold water areas. DVGW tested. DIN EN751-3. For fine thread DN < 10. Pressure: up to 20 bar. Temperature range: -60°C to +260°C		

thread sealants

			
1			
vm nr.	890097	Ref. No.	7004016
description	thread sealing LOCTITE 577 medium-strength bottle 50ml pipe thread sealing t.max. 150°C approval BAM and DVGW		
description	LOCTITE® 577™ - bottle 50ml It is designed for the locking and sealing of metal pipes and fittings as well as other cylindrical metal assemblies. The product provides an instant, low-pressure seal for metal pipes and fittings. It will not creep, shrink or block systems by shredding. Suitable for fast application at low temperatures. It has excellent chemical and thermal resistance and offers less migration of liquid product after application to the part.		

equipment-specific units

for coffee grinders

grinding burrs

screws

			
1			
vm nr.	560067	Ref. No.	8001031
description	flat-headed bolt thread M5 thread L 10mm SS DIN 7985/ISO 7045 Qty 20 pcs intake Phillips head ø 8mm head thickness 2mm		

for convection ovens/combi-steamers

drain units

drip rails

			
1			
vm nr.	692302	Ref. No.	2018000 2018006
description	drip rail L 500mm ABS plastic hole ø 5.5mm mounting distance 299mm for combi-steamer hose ø 15mm		
For models:	OEB10.10, OEB6.10, OES10.10, OES6.10, OGB10.10, OGB6.10, OGS10.10, OGS6.10		

			
1			
vm nr.	694425	Ref. No.	2616469
description	drip rail L 500mm plastic W 34mm hole ø 5mm for combi-steamer		
For models:	OEB10.10, OEB6.10, OES10.10, OES6.10, OGB10.10, OGB6.10, OGS10.10, OGS6.10		

			
1			
vm nr.	699355	Ref. No.	2556335
description	drip rail L 520mm W 25mm suitable for 6.10/10.10 Convotherm 4		

			
1			
vm nr.	699361	Ref. No.	2556345
description	drip rail push-in L 480mm plastic W 100mm for combi-steamer 6.10/10.10 Convotherm 4		



1

vm nr.	699356	Ref. No.	2556346
description	drip rail push-in L 685mm W 60mm H 95mm suitable for 6.20/10.20 Convotherm 4		

steam generators



1

vm nr.	692212	Ref. No.	2306118 2323768
description	steam generator W 610mm H 525mm D 115mm		



1

vm nr.	692593	Ref. No.	2016300
description	ventilation valve combi-steamer L 120mm W 120mm ø 43mm 12VDCV suitable for Mini series		
For models:	OES6.06		

injection nozzles



1

vm nr.	542356	Ref. No.	6005413
description	injection nozzle bore ø 1.5mm WS 14 T1: M10x1		



1

vm nr.	692594	Ref. No.	2226368 2230016
description	injection nozzle bore ø 1mm suitable for P3 D1 ø 10mm D2 ø 10mm L 130mm brass for steam generation mounting pos. left		
spare parts for	692594		
vm nr.	541508	Ref. No.	6006140
manometer ø 40mm pressure range 0-4bar connection thread 1/8"			
vm nr.	541806	Ref. No.	5009061 5009063
pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"			



1

vm nr.	692139	Ref. No.	2000027
description	injection nozzle bore ø 4mm L 40mm for combi-steamer T1: M10x1.5 T2: 3/4"		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	692768	Ref. No.	2223452
description	injection nozzle double with pressure switch and monometer bore ø 0.6mm D1 ø 10.5mm D2 ø 10.5mm L 60mm SS/brass for combi-steamer OES/OGS		
spare parts for	692768		
vm nr.	541508	Ref. No.	6006140
manometer ø 40mm pressure range 0-4bar connection thread 1/8"			
vm nr.	541806	Ref. No.	5009061 5009063
pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"			



1

vm nr.	692177	Ref. No.	2217332
description	injection nozzle with pressure switch and monometer bore ø 0.5mm D1 ø 12mm D2 ø 12mm L 60mm stainless steel for combi-steamer		
For models:	OEB6.10, OES6.06, OES6.10, OGB6.10, OGS6.10		
spare parts for	692177		
	vm nr.	541508	Ref. No. 6006140
	manometer ø 40mm pressure range 0-4bar connection thread 1/8"		
	vm nr.	541806	Ref. No. 5009061 5009063
	pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"		



1

vm nr.	692169	Ref. No.	2217333
description	injection nozzle with pressure switch and monometer bore ø 0.6mm D1 ø 12mm D2 ø 12mm L 60mm brass for combi-steamer		
For models:	OEB10.10, OEB10.20, OEB6.20, OES10.10, OES10.20, OES6.20, OGB10.10, OGB10.20, OGB6.20, OGS10.10, OGS10.20, OGS6.20		
spare parts for	692169		
	vm nr.	541508	Ref. No. 6006140
	manometer ø 40mm pressure range 0-4bar connection thread 1/8"		
	vm nr.	541806	Ref. No. 5009061 5009063
	pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"		



1

vm nr.	692592	Ref. No.	2217335
description	pressure monitor suitable for Mini series bore ø 1mm D1 ø 10mm D2 ø 10mm L 130mm brass for steam generation mounting pos. at the back right		
For models:	OEB20.10, OEB20.20, OES20.10, OES20.20, OGB20.10, OGB20.20, OGS20.10, OGS20.20		
spare parts for	692592		
	vm nr.	541508	Ref. No. 6006140
	manometer ø 40mm pressure range 0-4bar connection thread 1/8"		
	vm nr.	541806	Ref. No. 5009061 5009063
	pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"		

injection pipes



1

vm nr.	692746	Ref. No.	2225074 6015216
description	injection pipe for combi-steamer H 80mm with gasket and nut ED ø 10mm L 210mm thread M14x1		

spare parts and accessories



1

vm nr.	699829	Ref. No.	2004035
description	bracket for cable H 8.5mm ø 29mm M4		



1

vm nr.	699840	Ref. No.	6006081
description	drain plug for steam generator H 20mm 1 1/4"		

			
1			
vm nr.	112834	Ref. No.	6064078
description	gasket for burner chamber ø 140mm thickness 2mm graphite for combi-steamer suitable for CONVOTHERM 4 series 6.10/6.20/10.10		

			
1			
vm nr.	519625	Ref. No.	6056351
description	gasket for thermocouple ø 15mm ID ø 5mm H 1mm graphite suitable for combi-steamer series CONVOTHERM 4 Qty 5 pcs		

			
1			
vm nr.	699823	Ref. No.	6005427
description	grommet for ventilation H 9mm ø 83mm ID ø 53mm		

			
1			
vm nr.	692738	Ref. No.	2617294
description	mounting set for motor		

			
1			
vm nr.	699826	Ref. No.	6016030 6064077
description	sealing ring H 3.2mm ø 23mm ID ø 15mm		

filters

			
1			
vm nr.	700992	Ref. No.	6005024
description	drain filter ø 85mm for combi-steamer		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.20, OSP6.10		

front panels



1	vm nr.	692745	Ref. No.	2117301
	description	control panel model OES/OGS CONVOTHERM series P3 H 600mm W 160mm		



1	vm nr.	699847	Ref. No.	5056365
	description	housing L 245mm H 350mm D 35		



vm nr.	699846	Ref. No.	5056364
description	housing L 250mm H 350mm D 34		

cleaning system

nozzles



vm nr.	694801	Ref. No.	2611010
description	sprinkler nozzle thread M10 hole ø 3.5mm H 29.5mm SS CONVO-THERM		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

pumps



vm nr.	501563	Ref. No.	5056337
description	pump inlet ø 24 outlet ø 24 type UP30-494 200-240V 50/60Hz 1 phase 0.1kW L 146mm capacitor 2.5µF HANNING hose clamps		

hoses



vm nr.	542152	Ref. No.	2609347 2617594
description	extraction hose D1 ø 6.5mm D2 ø 10mm L 1700mm detergent		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



vm nr.	694798	Ref. No.	2054369 2609349 2617598
description	extraction hose D1 ø 6.5mm D2 ø 10mm L 1700mm rinse aid		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



vm nr.	694802	Ref. No.	7012302
description	hose ext. ø 9.8 D1 ø 6mm L 1300mm EPDM black Qty 1		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

screw connections



vm nr.	361914	Ref. No.	5011003
description	connecting piece 1/2" - 3/4" L 82mm plastic		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



pipes



1

vm nr.	699816	Ref. No.	6005300
description	connecting fitting L 210mm for water inlet		

non-return valves



1

vm nr.	531322	Ref. No.	6056934
description	backflow preventer for boiler L 88mm connection 10.5/13.5 hose ø 3/4" mm for combi-steamer CONVOTHERM 4		

hoses



1

vm nr.	506274	Ref. No.	5064082
description	formed hose end piece A ext. ø 28mm end piece A int. ø 22mm AD2 ø 28mm ø end piece B 22mm L 555mm boiler silicone combi-steamer L-shape white		



1

vm nr.	699367	Ref. No.	6064052
description	formed hose int. ø 1 47mm int. ø 2 30mm ED ø 54mm ext. ø 36 L 100mm for combi-steamer		



1

vm nr.	530897	Ref. No.	2364047
description	hose ID ø 10mm ED ø 15mm for boiler suitable for combi-steamer CONVOTHERM 4		



1

vm nr.	699850	Ref. No.	2006056
description	inlet spout L 365mm connection 3/4"		

service kits



1

vm nr.	551407	Ref. No.	8056358
description	mounting set control PCB M4 suitable for CONVOTHERM 4		



1

vm nr.	699818	Ref. No.	5008050
description	mounting set for fan CONVOTHERM		



1

vm nr.	699819	Ref. No.	2617293
description	mounting set for fan wheel CONVOTHERM		



1

vm nr.	699369	Ref. No.	2556368
description	repair kit for door drip tray combi-steamer CONVOTHERM 4		



1

vm nr.	699815	Ref. No.	2618161 6015032
description	seal kit for burner 12-20kW		



1

vm nr.	530896	Ref. No.	6056327
description	seal kit suitable for CONVOTHERM 4		

h3>drip water trays



1

vm nr.	699831	Ref. No.	2004051
description	drip tray L 535mm W 250mm H 40mm		



1

vm nr.	699236	Ref. No.	2616470
description	drip tray L 710mm W 28mm H 22mm		



1

vm nr.	699848	Ref. No.	2556336
description	drip tray L 725mm W 25mm H 22mm		

h3>door mechanics

h4>holders



1

vm nr.	692792	Ref. No.	6056812
description	bracket L 32mm W 30mm H 26mm stainless steel suitable for combi-steamer series CONVOTHERM 4		

h4>rollers



1

vm nr.	694333	Ref. No.	2117291
description	roller set ø 60mm W 27.5mm V-shape stainless steel old edition		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	694604	Ref. No.	2619141
description	roller set U-shape stainless steel new edition		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

h3>door bumpers



1

vm nr.	699240	Ref. No.	6056370 6056370A
description	door bumper ø 12mm H 10mm Qty 4		



vm nr.	694399	Ref. No.	8009056	
description	door bumper set 2-piece silicone for combi-steamer ø 20mm			
For models:	OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10			
spare parts for	694399			
	vm nr.	694398	Ref. No.	2004195
	door bumper silicone for combi-steamer ø 20mm			

h3>accessories

			
vm nr.	694398	Ref. No.	2004195
description	door bumper silicone for combi-steamer ø 20mm		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG12.20, OSG20.20, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
vm nr.	694797	Ref. No.	2619155
description	guide bar W 30mm plastic L 83.5mm black H 19mm incl. screws, nuts and film		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

			
vm nr.	694803	Ref. No.	2619154 6012008 6012016
description	rail W 25mm plastic L 188mm black H 45mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

h2>EQUIPMENT-SPECIFIC UNITS CONVOTHERM

			
vm nr.	692794	Ref. No.	2664000
description	stop for guide bar W 20mm L 80mm plastic/rubber suitable for combi-steamer CONVOTHERM		

			
vm nr.	694799	Ref. No.	2619156 6015226
description	stop W 25mm plastic L 60mm black H 20mm incl. screws, nuts and film		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

h3>vibration pumps

			
vm nr.	500580	Ref. No.	5008011 5008011K 5030635
description	vibration pump 230V 60W 50/60Hz inlet ø 7 outlet ø 1/8" IT CEME type E512 with accessories duty cycle 1/2 ambient temperature max. 60°C medium temp max. 35°C overheating protection 110°C CleanJet		

h3>heat exchangers

			
1			
vm nr.	520995	Ref. No.	6064017
description	gasket for heat exchanger L 65mm W 65mm hole distance 51mm graphite 50 model CONVOTHERM 4 thickness 2mm		

			
1			
vm nr.	520994	Ref. No.	6064018
description	gasket for heat exchanger L 89mm W 89mm hole distance 70mm graphite 70 model CONVOTHERM 4 thickness 2mm		



			
1			
vm nr.	692597	Ref. No.	2010000 2617317 2623208
description	heat exchanger combi-steamer CONVOTHERM		
For models:	OGB10.10, OGB20.10, OGS10.10, OGS20.10		

miscellaneous

			
1			
vm nr.	523050	Ref. No.	6016500
description	backflow preventer plastic operating medium water for steam generator		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

			
1			
vm nr.	530777	Ref. No.	2002042
description	bracket for spray gun L 96mm W 75mm H 50mm		
accessories for	530777		
	vm nr.	540158	Ref. No. 6005005
	spray gun for appliances 1/2" ET type ECHTERMANN		

			
1			
vm nr.	699238	Ref. No.	6006030
description	connecting piece with nozzle outlet (with nozzle) L 60mm bore ø 0.5mm for hose 10mm		

			
1			
vm nr.	506225	Ref. No.	6012050
description	door bumper		
For models:	OES6.06		

			
1			
vm nr.	694399	Ref. No.	8009056
description	door bumper set 2-piece silicone for combi-steamer ø 20mm		
For models:	OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		
spare parts for	694399		
	vm nr.	694398	Ref. No. 2004195
	door bumper silicone for combi-steamer ø 20mm		

			
1			
vm nr.	694440	Ref. No.	2618810
description	drip rail L 500mm plastic W 30mm		
For models:	OES6.06		

			
1			
vm nr.	699235	Ref. No.	6056326
description	flap for dehumidification L 155mm W 94mm H 124mm 220VAC		
spare parts for	699235		
	vm nr.	530896	Ref. No. 6056327
	seal kit suitable for CONVOTHERM 4		



1



vm nr.	692171	Ref. No.	5005020
description	frame for lamp lenses bore ø 6.3mm D1 ø 72mm D2 ø 56mm L 83mm W 83mm thickness 1mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

1



vm nr.	902415	Ref. No.	7011010
description	gasket for control panel profile W 155mm L 600mm suitable for CONVOTHERM self-adhesive Qty		

1



vm nr.	699839	Ref. No.	6015236
description	guide L 51.5mm W 24mm H 12mm hole ø 4mm		

1



vm nr.	512478	Ref. No.	5011002
description	hose connector thread 3/4" connection distance 75mm		

1



vm nr.	699358	Ref. No.	6056827
description	pressure compensation valve complete, with solenoid coil for combi-steamer L 155mm D1 ø 58.3mm W 98mm H 122mm D2 ø 54mm 220V 15W duty cycle 100%		

1



vm nr.	696398	Ref. No.	2611068 2611184 2616460 2627250
description	rotary nozzle for combi-steamer bore ø 1.1/1.5mm L 155mm thread 1/8"		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

1



vm nr.	696361	Ref. No.	6005299
description	sleeve for drain pump bore ø 18mm D1 ø 20mm D2 ø 22mm L 25mm SS thickness 1mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

1



vm nr.	692170	Ref. No.	6015200
description	spacer for door L 24mm thread M4 ø 20mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

1



vm nr.	699849	Ref. No.	2056497
description	spacer for tray rack trolley L 90mm W 13mm H 13mm		



1

vm nr.	750528	Ref. No.	2608962
description	ventilation valve D1 ø 56mm D2 ø 60mm L 57.6mm SS mounting pos. upper ø 48mm hose ø 1.48mm Qty 1 pcs		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		
spare parts for	750528		
	vm nr.	532638	Ref. No. 6005068
O-ring silicone thickness 5.34mm ID ø 43.82mm Qty 1 pcs			
accessories for	750528		
	vm nr.	699823	Ref. No. 6005427
grommet for ventilation H 9mm ø 83mm ID ø 53mm			

knobs

universal knobs

			
1			
vm nr.	110167	Ref. No.	6003011
description	knob time 90min t.max.°C ø 50mm shaft ø 6x4.6mm shaft flat lower black		
For models:	AR100, AR108, AR12, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, AR8, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		

			
1			
vm nr.	110165	Ref. No.	6003010
description	knob switch zero mark ø 42mm shaft ø 6x4.6mm shaft flat upper black		
For models:	AR108, AR12, AR18, AR28, AR40, AR54, AR72, AR8, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

producer-specific knobs

CONVOTHERM

			
1			
vm nr.	110165	Ref. No.	6003010
description	knob switch zero mark ø 42mm shaft ø 6x4.6mm shaft flat upper black		
For models:	AR108, AR12, AR18, AR28, AR40, AR54, AR72, AR8, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

			
1			
vm nr.	112565	Ref. No.	5009313 5009314 5009320
description	knob t.max.°C ø 44mm shaft flat special black for combi-steamer		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20...(Other models you can see in the webshop)		

			
1			
vm nr.	110167	Ref. No.	6003011
description	knob time 90min t.max.°C ø 50mm shaft ø 6x4.6mm shaft flat lower black		
For models:	AR100, AR108, AR12, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, AR8, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		

			
1			
vm nr.	112816	Ref. No.	5056360
description	knob without symbol shaft ø 6.5x6mm black combi-steamer CONVOTHERM 4		



miscellaneous



vm nr.	112565	Ref. No.	5009313 5009314 5009320
description	knob t.max.°C ø 44mm shaft flat special black for combi-steamer		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.10, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20...(Other models you can see in the webshop)		

accessories

gaskets



vm nr.	112623	Ref. No.	5009108
description	gasket for shaft ø6x4.6		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

locks

turning lever locks

universal

RAHRBACH



vm nr.	690027	Ref. No.	6002048 6002048K
description	handle latch left L 150mm H 59mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		
accessories for	690027		
	vm nr.	690045	Ref. No. —
door catch mounting pos. left off-set 20mm L 110mm H 56mm W 33mm mounting distance 68/68mm zinc die cast series 6300			
	vm nr.	690135	Ref. No. 6002049 6002049K
door catch mounting pos. left off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm zinc die cast series 1750			
	vm nr.	690137	Ref. No. 6002060
sliding plate mounting pos. left L 28mm H 3mm W 21mm H2 12.5mm			



vm nr.	690500	Ref. No.	6002053 6002053K
description	handle latch right L 185mm H 66mm handle material plastic type 6300 series		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10, UG10.20		
spare parts for	690500		
	vm nr.	699841	Ref. No. 6002056
cover cap for turning lever lock ø 32mm H 14mm			
accessories for	690500		
	vm nr.	514281	Ref. No. —
base plate L 110mm W 35mm for door catch thickness 10mm			
	vm nr.	690136	Ref. No. 6002062
sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm			
	vm nr.	691174	Ref. No. —
counterpart L 90mm W 60mm for door latch			
	vm nr.	700091	Ref. No. —
door catch mounting pos. right off-set 20mm L 110mm H 56mm W 33mm mounting distance 68/68mm zinc die cast series 6300			
	vm nr.	700098	Ref. No. 6002054 6002054K
door catch mounting pos. right off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm series 1750			

vm nr.	690135	Ref. No.	6002049 6002049K
description	door catch mounting pos. left off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm zinc die cast series 1750		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		
spare parts for	690135		
	vm nr.	690137	Ref. No. 6002060
sliding plate mounting pos. left L 28mm H 3mm W 21mm H2 12.5mm			



1

vm nr.	700098	Ref. No.	6002054 6002054K
description	door catch mounting pos. right off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm series 1750		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSG12.20, OSG20.20, OSG6.10, UG10.20		
accessories for	700098		
vm nr.	514281	Ref. No.	—
base plate L 110mm W 35mm for door catch thickness 10mm			



			
vm nr.	690137	Ref. No.	6002060
description	sliding plate mounting pos. left L 28mm H 3mm W 21mm H2 12.5mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		

			
vm nr.	690136	Ref. No.	6002062
description	sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

STUV



1

vm nr.	700098	Ref. No.	6002054 6002054K
description	door catch mounting pos. right off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm series 1750		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSG12.20, OSG20.20, OSG6.10, UG10.20		
spare parts for	700098		
	vm nr.	690136	Ref. No. 6002062
	 sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm		
accessories for	700098		
	vm nr.	514281	Ref. No. —
	 base plate L 110mm W 35mm for door catch thickness 10mm		

producer-specific

CONVOTHERM

			
vm nr.	691987	Ref. No.	2216070 2216070K 2230605 6012001 CV2216070
description	door catch with magnetic switch		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	691986	Ref. No.	2525040 6012000
description	handle latch right L 200mm handle material plastic		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		
accessories for	691986		
	vm nr.	691987	Ref. No.
			2216070 2216070K 2230605 6012001 CV2216070
door catch with magnetic switch			

1



vm nr.	690768	Ref. No.	6002043	
description	mounting set for turning lever lock			
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10, UG10.20			
accessories for	690768			
	vm nr.	690027	Ref. No.	6002048 6002048K
handle latch left L 150mm H 59mm				
	vm nr.	690044	Ref. No.	—
handle latch right L 185mm H 59mm handle material plastic type 6300 series				



vm nr.	690027	Ref. No.	6002048 6002048K
description	handle latch left L 150mm H 59mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		
accessories for	690027		
	vm nr.	690045	Ref. No. —
	door catch mounting pos. left off-set 20mm L 110mm H 56mm W 33mm mounting distance 68/68mm zinc die cast series 6300		
	vm nr.	690135	Ref. No. 6002049 6002049K
	door catch mounting pos. left off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm zinc die cast series 1750		
	vm nr.	690137	Ref. No. 6002060
	sliding plate mounting pos. left L 28mm H 3mm W 21mm H2 12.5mm		



vm nr.	690500	Ref. No.	6002053 6002053K
description	handle latch right L 185mm H 66mm handle material plastic type 6300 series		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10, UG10.20		
spare parts for	690500		
	vm nr.	699841	Ref. No. 6002056
	cover cap for turning lever lock ø 32mm H 14mm		
accessories for	690500		
	vm nr.	514281	Ref. No. —
	base plate L 110mm W 35mm for door catch thickness 10mm		
	vm nr.	690136	Ref. No. 6002062
	sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm		
	vm nr.	691174	Ref. No. —
	counterpart L 90mm W 60mm for door latch		
	vm nr.	700091	Ref. No. —
	door catch mounting pos. right off-set 20mm L 110mm H 56mm W 33mm mounting distance 68/68mm zinc die cast series 6300		

accessories for	690500		
	vm nr.	700098	Ref. No. 6002054 6002054K
	door catch mounting pos. right off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm series 1750		



vm nr.	690204	Ref. No.	6002064
description	base plate for door catch thickness 10mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD12.20, OD20.10, OD20.20		



vm nr.	690203	Ref. No.	6002066
description	base plate for door catch thickness 6mm		
For models:	OD10.10, OD10.20, OD6.10		



vm nr.	699841	Ref. No.	6002056
description	cover cap for turning lever lock ø 32mm H 14mm		



vm nr.	690135	Ref. No.	6002049 6002049K
description	door catch mounting pos. left off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm zinc die cast series 1750		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		
spare parts for	690135		



vm nr.	690137	Ref. No.	6002060
description	sliding plate mounting pos. left L 28mm H 3mm W 21mm H2 12.5mm		



vm nr.	690137	Ref. No.	6002060
description	sliding plate mounting pos. left L 28mm H 3mm W 21mm H2 12.5mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		



vm nr.	690136	Ref. No.	6002062
description	sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

handle latches

universal

inside fixing

locks



vm nr.	694054	Ref. No.	2518784
description	door handle for headed units L 145mm W 40mm H 62mm spring length 33mm inner black		
For models:	OES6.06		
spare parts for	694054		
	vm nr.	514390	Ref. No. —
spring for door handle ø 6mm L 54mm W 27.5mm			
	vm nr.	694675	Ref. No. —
door catch L 88mm W 40mm H 37mm spring length 33mm mounting distance 60mm			
	vm nr.	694734	Ref. No. —
door handle L 165mm W 40mm H 25mm black			
	vm nr.	694735	Ref. No. —
cap ø 32mm black			
accessories for	694054		
	vm nr.	691123	Ref. No. —
duct for door opener			
	vm nr.	694055	Ref. No. —
door catch L 25mm W 14mm total length 54mm thread M8 thread L 29mm			
	vm nr.	694066	Ref. No. —
door catch with spigot 2-stage L 28mm W 14mm H 15mm H1 16mm total length 51mm thread M8 thread L 23mm stainless steel			
	vm nr.	694067	Ref. No. —
door catch with spigot 1-stage L 26mm total length 51mm thread M8			

producer-specific

CONVOTHERM



vm nr.	694948	Ref. No.	6056498
description	door catch L 30mm W 14mm H 13mm cast iron with spigot mounting thread M4		



vm nr.	694949	Ref. No.	6056807
description	door catch L 34.5mm W 14.5mm H 13mm cast iron with spigot mounting thread M4		



vm nr.	694947	Ref. No.	6056499
description	door catch L 58mm W 20mm H 17mm cast iron with spigot mounting thread M5 IT		



vm nr.	694054	Ref. No.	2518784
description	door handle for headed units L 145mm W 40mm H 62mm spring length 33mm inner black		
For models:	OES6.06		
spare parts for	694054		
	vm nr.	514390	Ref. No. —
spring for door handle ø 6mm L 54mm W 27.5mm			
	vm nr.	694675	Ref. No. —
door catch L 88mm W 40mm H 37mm spring length 33mm mounting distance 60mm			
	vm nr.	694734	Ref. No. —
door handle L 165mm W 40mm H 25mm black			
	vm nr.	694735	Ref. No. —
cap ø 32mm black			
accessories for	694054		
	vm nr.	691123	Ref. No. —
duct for door opener			
	vm nr.	694055	Ref. No. —
door catch L 25mm W 14mm total length 54mm thread M8 thread L 29mm			
	vm nr.	694066	Ref. No. —
door catch with spigot 2-stage L 28mm W 14mm H 15mm H1 16mm total length 51mm thread M8 thread L 23mm stainless steel			
	vm nr.	694067	Ref. No. —
door catch with spigot 1-stage L 26mm total length 51mm thread M8			



1

vm nr.	692741	Ref. No.	6056809
description	door handle L 195mm W 53mm H 62mm clamp length 42mm black mounting thread M4 CONVOTHERM model C4 Serie		




1

vm nr.	694919	Ref. No.	6050978 6056384
description	door handle L 195mm W 53mm H 62mm spring length 44mm blue mounting distance 30mm mounting thread M4		

hinges

overlying hinges

STUV




1

vm nr.	700092	Ref. No.	6001031 6001031K
description	hinge off-set 0mm overall height 21mm type 3.50.0139.0 total length 110mm W 80mm face mounted		
For models:	AR12, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR8, UG6.05, UG6.10		

piano hinges


producer-specific

CONVOTHERM



1

vm nr.	690074	Ref. No.	6001041 6001041K
description	hinge L 109mm W 85mm H 16mm mounting distance 65/70mm mounting distance 1 43/30mm hole ø 5.5mm thickness 3mm stainless steel		
For models:	AR108, HUD12.20, HUD20.10, HUD20.20, OD12.20, OD20.10, OD20.20		



1

vm nr.	690214	Ref. No.	6001032 6001032K
description	hinge L 90mm W 85mm H 16mm mounting distance 66/55mm mounting distance 1 43/25mm hole ø 6mm thickness 3mm stainless steel		
For models:	HUD10.10, HUD6.10, OD10.10, OD10.20, OD6.10, OS10.10, OS10.20, OS6.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, OSP6.10		

door bearing



1

vm nr.	699842	Ref. No.	2517296 2517297 2523667
description	hinge L 128mm W 29mm H 23.5mm mounting pos. upper and bottom thickness 10.5mm bolt 17mm bolt ø 10mm series P3 1 pair		



1

vm nr.	692788	Ref. No.	2656839
description	hinge mounting pos. lower bolt 18mm bolt ø 10mm hinged at right series CONVOTHERM 4		



			
1			
vm nr.	692790	Ref. No.	6056843
description	hinge mounting pos. lower ID ø 10mm hinged at right series CONVO-THERM 4		

			
1			
vm nr.	692791	Ref. No.	6056842
description	hinge mounting pos. upper ID ø 10mm bolt 19.5mm bolt ø 9.5mm hinged at right series CONVOTHERM 4		

			
1			
vm nr.	692793	Ref. No.	6056845
description	hinge mounting pos. lower ID ø 10mm hinged at right suitable for combi-steamer series CONVOTHERM 4		

			
1			
vm nr.	699843	Ref. No.	2014003
description	hinge camp L 47mm W 28mm H 9mm mounting distance 22mm mounting pos. upper		

miscellaneous

			
1			
vm nr.	692784	Ref. No.	6056841
description	hinge mounting pos. right bottom thickness 5mm bolt 18.5mm bolt ø 10mm hinged at right suitable for CONVOTHERM 4		

			
1			
vm nr.	699844	Ref. No.	2014007
description	hinge curved L 38mm W 23mm		

			
1			
vm nr.	692785	Ref. No.	6056840
description	hinge mounting pos. upper bolt 13mm bolt ø 10mm series CONVO-THERM 4 hinged at right		

equipment feet and end caps

bullet feet

zamak/SS

			
1			
vm nr.	692789	Ref. No.	2656838
description	hinge mounting pos. upper bolt 17mm bolt ø 10mm hinged at right series CONVOTHERM 4		

			
1			
vm nr.	750715	Ref. No.	6014042
description	bullet foot L 40mm W 40mm H 75-105mm Qty 1 pcs		

bolting feet

			
1			
vm nr.	692786	Ref. No.	6056844
description	hinge mounting pos. upper ID ø 10mm bolt 18mm bolt ø 18mm series CONVOTHERM 4 hinged at right		

			
1			
vm nr.	699852	Ref. No.	6056353
description	equipment foot L 150mm W 50mm H 100mm bore ø 8.5mm Qty 1 pcs		

miscellaneous

with spigot

ø125mm



1

vm nr.	710013	Ref. No.	6004066
description	fixed castor ø 125mm M10 housing SS H 157mm wheel width 32mm		
For models:	AR108, HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OS12.20, OS20.10, OS20.20, OSC12.20, OSC20.10, OSC20.20, OSG12.20, OSG20.20, OSP12.20, OSP20.10, OSP20.20		



1

vm nr.	710021	Ref. No.	3303456 6004056
description	swivel castor ø 125mm housing SS		
For models:	AR108, HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OS12.20, OS20.10, OS20.20, OSC12.20, OSC20.10, OSC20.20, OSG12.20, OSG20.20, OSP12.20, OSP20.10, OSP20.20		

BLICKLE

stainless steel

ø125mm



1

vm nr.	701021	Ref. No.	6014051
description	fixed castor ø 125mm plates fixing 57x48mm housing SS bearing slide bearing H 155mm wheel width 32mm		
For models:	OEB12.20, OEB20.10, OEB20.20, OES12.20, OES20.10, OES20.20, OGB12.20, OGB20.10, OGB20.20, OGS12.20, OGS20.10, OGS20.20		



1

vm nr.	701022	Ref. No.	6014050
description	swivel castor ø 125mm bolt hole ø13.0mm housing SS bearing slide bearing H 158mm wheel width 32mm		
For models:	OEB12.20, OEB20.10, OEB20.20, OES12.20, OES20.10, OES20.20, OGB12.20, OGB20.10, OGB20.20, OGS12.20, OGS20.10, OGS20.20		




1

vm nr.	701023	Ref. No.	6014052
description	swivel castor with swivel brake ø 125mm bolt hole ø13.0mm housing SS bearing slide bearing H 158mm wheel width 32mm		
For models:	OEB12.20, OEB20.10, OEB20.20, OES12.20, OES20.10, OES20.20, OGB12.20, OGB20.10, OGB20.20, OGS12.20, OGS20.10, OGS20.20		

gaskets


gaskets for heated units

window seals




1

vm nr.	901430	Ref. No.	7001040
description	window gasket profile 1502 Qty supplied by meter		
For models:	AR12, AR18, AR8, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		




1

vm nr.	900113	Ref. No.	7001041
description	window gasket profile 1560 Qty supplied by meter		
For models:	AR12, AR18, AR28, AR8, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		



1


vm nr.	900448	Ref. No.	7001045
description	window gasket profile 1630 L 1800mm Qty 1		
For models:	OD10.10, OD6.10, OSG10.10, OSG6.10		




1

vm nr.	900114	Ref. No.	7001042
description	window gasket profile 1870 Qty supplied by meter		
For models:	AR28, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		


door seals




vm nr.	900062	Ref. No.	7001017 7001071
description	door seal profile 2060 L 720mm W 625mm Qty 1 outer plug size suitable for CONVOTHERM		
For models:	HUD10.10, OD10.10, OS10.10, OSC10.10, OSC10.20, OSC6.10, OSP10.10, OSP10.20, UG10.10		




vm nr.	900057	Ref. No.	7001013
description	door seal profile 2060 Qty supplied by meter		
For models:	AR72, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		




vm nr.	900061	Ref. No.	7001016
description	door seal profile 2060 W 480mm L 625mm outer plug size Qty 1 suitable for CONVOTHERM 6 x 1/1		
For models:	HUD6.10, OD10.10, OD10.20, OD6.10, OS6.10, OSC6.10, OSP6.10, UG6.10		




vm nr.	900950	Ref. No.	7001032
description	door seal profile 2060 W 625mm L 810mm outer plug size suitable for CONVOTHERM OD/OS		
For models:	OD10.20, OS10.20, OSC10.20, OSP10.20		




vm nr.	901145	Ref. No.	7001050
description	door seal profile 2060 W 686mm L 770mm outer plug size Qty 1 suitable for CONVOTHERM		
For models:	OD10.20, OD12.20		




vm nr.	900064	Ref. No.	7001019 7001020
description	door seal profile 2060 W 705mm L 1080mm outer plug size Qty 1 suitable for CONVOTHERM short side open		
For models:	HUD12.20, OD10.20, OD12.20, OD20.10, OD20.20, OS12.20, OSC12.20, OSP12.20, UG20.20		



vm nr.	900063	Ref. No.	7001018 7001074
description	door seal profile 2060 W 705mm L 1635mm external size Qty 1 short side open		
For models:	AR100, HUD20.10, HUD20.20, OD20.10, OD20.20, OS20.10, OS20.20, OSC20.10, OSC20.20, OSP20.10, OSP20.20, UG20.10		




vm nr.	901289	Ref. No.	7001051
description	door seal profile 2060 W 710mm L 1300mm outer plug size Qty 1 suitable for CONVOTHERM OD20.20 Gas		
For models:	OD20.20		




1

vm nr.	900443	Ref. No.	7001034
description	door seal profile 2420 W 450mm L 460mm outer plug size Qty 1 suitable for CONVOTHERM		
For models:	OD6.10, OSG6.10		



1

vm nr.	900444	Ref. No.	7001035
description	door seal profile 2420 W 450mm L 700mm outer plug size Qty 1 suitable for CONVOTHERM		
For models:	OD10.10, OSG10.10		



1

vm nr.	901177	Ref. No.	7011051(Alternativ) 7011054(Alternativ)
description	door seal profile 2480 L 1470mm suitable for CONVOTHERM welded		




1

vm nr.	901951	Ref. No.	7011051 7011054 7011060
description	door seal profile 2480 L 1485mm Qty 1 suitable for CONVOTHERM series P3 for model OES 6.06/6.10 mini		
For models:	OES6.06		




1

vm nr.	902429	Ref. No.	7011052 7011055 7011061
description	door seal profile 2480 L 1880mm Qty 1 suitable for CONVOTHERM model OES 10.10 mini series C4		




1

vm nr.	901398	Ref. No.	7001079
description	door seal profile 2519 W 695mm L 1410mm external size Qty 1		
For models:	OSG20.20		




1

vm nr.	901393	Ref. No.	7001078
description	door seal profile 2519 W 695mm L 885mm external size suitable for CONVOTHERM		
For models:	OSG12.20		




1

vm nr.	902424	Ref. No.	7011003
description	door seal profile 2715 W 460mm H 1495mm outer plug size Qty 1 for model 20.10 series P3 CONVOTHERM		



1

vm nr.	902423	Ref. No.	7011001
description	door seal profile 2715 W 460mm H 510mm outer plug size Qty 1 for model 6.10 series P3 CONVOTHERM		



1

vm nr.	902422	Ref. No.	7011002
description	door seal profile 2715 W 460mm H 770mm outer plug size Qty 1 for model 10.10 series P3 CONVOTHERM		

vm nr.	902428	Ref. No.	7011007
description	door seal profile 2715 W 670mm H 1495mm outer plug size Qty 1 for model 20.20 series P3 CONVOTHERM		

vm nr.	902416	Ref. No.	7056338
description	door seal profile 2717 W 460mm H 490mm outer plug size Qty 1 CONVOTHERM 6.10 C4 Serie		

vm nr.	902426	Ref. No.	7011004
description	door seal profile 2715 W 670mm H 550mm outer plug size Qty 1 for model 6.20 series P3 CONVOTHERM		

vm nr.	902393	Ref. No.	7056340
description	door seal profile 2717 W 460mm H 760mm outer plug size Qty 1 CONVOTHERM 10.10 C4 Serie		

vm nr.	902425	Ref. No.	7011005
description	door seal profile 2715 W 670mm H 770mm outer plug size Qty 1 for model 10.20 series P3 CONVOTHERM		


vm nr.	902430	Ref. No.	7056339
description	door seal profile 2717 W 490mm H 660mm outer plug size Qty 1 CONVOTHERM 6.20 C4 Serie		

vm nr.	902427	Ref. No.	7011006
description	door seal profile 2715 W 670mm H 965mm outer plug size Qty 1 for model 12.20 series P3 CONVOTHERM		

vm nr.	902432	Ref. No.	7056342
description	door seal profile 2717 W 660mm H 960mm outer plug size Qty 1 CONVOTHERM 12.20 C4 Serie		


vm nr.	902433	Ref. No.	7056343
description	door seal profile 2717 W 460mm H 1495mm outer plug size Qty 1 CONVOTHERM 20.10 C4 Serie		

vm nr.	902394	Ref. No.	7056344
description	door seal profile 2717 W 665mm H 1490mm outer plug size Qty 1 CONVOTHERM 20.20 C4 Serie		




vm nr.	902431	Ref. No.	7056341
description	door seal profile 2717 W 66mm H 760mm outer plug size Qty 1 CONVOTHERM 10.20 C4 Serie		

gaskets for tray rack trolleys



vm nr.	900167	Ref. No.	7001039 7001039K
description	tray rack trolley gasket profile 4030 L 1970mm Qty 1 silicone transparent		
For models:	HUD12.20, HUD20.10, HUD20.20, OD12.20, OD20.10, OD20.20, OS12.20, OS20.10, OS20.20, OSC12.20, OSC20.10, OSC20.20, OSP12.20, OSP20.10, OSP20.20, UG10.10, UG10.20, UG20.10, UG20.20		




vm nr.	901150	Ref. No.	7011000
description	tray rack trolley gasket profile 4080 L 540mm Qty 1		
For models:	OEB20.10, OES20.10, OGB20.10, OGS20.10		
accessories for	901150		
	vm nr.	560067	Ref. No. 8001031
flat-headed bolt thread M5 thread L 10mm SS DIN 7985/ISO 7045 Qty 20 pcs intake Phillips head ø 8mm head thickness 2mm			




vm nr.	901833 ¹	Ref. No.	2514386 2525227
description	tray rack trolley gasket profile 4085 L 535mm Qty 1 incl. fastening strip		
For models:	OEB20.10, OES20.10, OGB20.10, OGS20.10		


¹incl. mounting rail




vm nr.	901574	Ref. No.	7011009
description	tray rack trolley gasket profile 4085 L 540mm Qty 1		




vm nr.	902338	Ref. No.	7056806
description	tray rack trolley gasket profile 4085 L 570mm Qty 1		



vm nr.	901749	Ref. No.	2514385 2525226 7001077
description	tray rack trolley gasket profile 4085 L 725mm Qty 1 incl. fastening strip		
For models:	OEB12.20, OEB20.20, OES12.20, OES20.20, OGB12.20, OGB20.20, OGS12.20, OGS20.20		



vm nr.	902441	Ref. No.	7011008
description	tray rack trolley gasket profile 4085 L 740mm Qty 1		



vm nr.	902339	Ref. No.	7056805
description	tray rack trolley gasket profile 4085 L 780mm Qty 1		

gaskets for control panels



vm nr.	902415	Ref. No.	7011010
description	gasket for control panel profile W 155mm L 600mm suitable for CONVOTHERM self-adhesive Qty		

miscellaneous


miscellaneous




vm nr.	902417	Ref. No.	7003066
description	sealing strip Qty supplied by meter self-adhesive suitable for CONVOTHERM size 9x3mm		

O-rings


EPDM



vm nr.	532674	Ref. No.	6005236
description	O-ring EPDM thickness 3mm ID ø 53mm Qty 1 pcs		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		




vm nr.	532673	Ref. No.	6015000 6015010
description	O-ring EPDM thickness 4mm ID ø 67mm Qty 1 pcs		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		




vm nr.	510408	Ref. No.	6005015
description	O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		


silicone



vm nr.	532374	Ref. No.	6005068
description	O-ring silicone thickness 5.34mm ID ø 43.82mm Qty 10 pcs		



vm nr.	532575	Ref. No.	6005069
description	O-ring silicone thickness 5.34mm ID ø 59.69mm Qty 1 pcs		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		




vm nr.	696759	Ref. No.	6056349
description	O-ring silicone thickness 5mm ID ø 44mm Qty 5 pcs		

sealing washers

fibre gaskets



vm nr.	510416	Ref. No.	6005016
description	flat gasket fibre ED ø 19mm ID ø 10.5mm thickness 1.5mm for thread M10 Qty 1 pcs		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



vm nr.	510406	Ref. No.	6005065
description	flat gasket fibre ED ø 60mm ID ø 48mm thickness 3mm for thread 1½" Qty 1 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

graphite gaskets



vm nr.	691609	Ref. No.	6015028
description	gasket graphite ED ø 150mm ID ø 115mm thickness 2mm Qty 1 pcs		
For models:	OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	521012	Ref. No.	6005260
description	gasket graphite ED ø 15mm ID ø 5mm thickness 1.2mm Qty 1 pcs		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG20.20, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



2

vm nr.	514439	Ref. No.	6015034
description	gasket graphite ED ø 82.5mm ID ø 52.5mm thickness 2mm		
For models:	OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

plastic gaskets



1

vm nr.	510670	Ref. No.	6005407
description	gasket plastic ED ø 20mm ID ø 15mm thickness 2.9mm Qty 1 pcs		
For models:	OEB6.10, OES6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

copper gaskets

DIN-7603-C



1

vm nr.	510420	Ref. No.	6005055
description	gasket copper ED ø 19.9mm ID ø 14.3mm thickness 2mm Qty 1 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20...(Other models you can see in the webshop)		

paper gasket



1

vm nr.	512427	Ref. No.	6005025
description	gasket paper ED ø 54mm ID ø 42.5mm thickness 2mm Qty 1 pcs ø 1 1/4"mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES6.10, OES6.20, OGB10.10, OGB6.10, OGB6.20, OGS10.10, OGS6.10, OGS6.20		

silicone gaskets



1

vm nr.	693168	Ref. No.	6005074
description	gasket silicone ED ø 44mm ID ø 4mm thickness 5mm Qty 1 pcs		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



1

vm nr.	359721	Ref. No.	5005025
description	gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, UG10.10, UG10.20, UG20.10, UG20.20, UG4.05, UG6.05, UG6.10		

Viton gaskets



1

vm nr.	510577	Ref. No.	6005081
description	flat gasket Viton ED ø 7.5mm ID ø 1mm thickness 5mm Qty 1 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10		

shaft gaskets

miscellaneous



1

vm nr.	694646	Ref. No.	2617295
description	shaft sealing set for hot air motors		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		


special gaskets

for combi-steamers




1

vm nr.	560644	Ref. No.	6056494
description	boot for drain pan ED ø 60mm ID ø 44mm CONVOTHERM 4		



1

vm nr.	699822	Ref. No.	6015029
description	gasket for burner chamber ED ø 170mm ID ø 134mm graphite thickness 2mm		



1

vm nr.	699825	Ref. No.	6015030
description	gasket L 63mm W 63mm for flues ID ø 42mm graphite thickness 2mm hole distance 50mm		



1

vm nr.	560636	Ref. No.	6064079
description	gasket suitable for CONVOTHERM burner L 150mm W 150mm with mounting accessories graphite thickness 2mm 10.20/20.20		



1

vm nr.	560643	Ref. No.	6056943
description	gasket suitable for CONVOTHERM combi-steamer L 90mm W 29mm with mounting kit graphite thickness 2mm		



1

vm nr.	699239	Ref. No.	6005067
description	sealing disc ED ø 36mm thickness 5mm aperture 5mmmm		

miscellaneous



1

vm nr.	514439	Ref. No.	6015034
description	gasket graphite ED ø 82.5mm ID ø 52.5mm thickness 2mm		
For models:	OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	521013	Ref. No.	2623226 6015025
description	gasket set suitable for CONVOTHERM for heating element L 90mm W 71mm Qty 1m graphite hole distance 54/74mm		
For models:	OEB10.10, OEB20.10, OEB6.10, OEB6.20, OES10.10, OES20.10, OES6.10, OES6.20		



1

vm nr.	510086	Ref. No.	2006010
description	gasket suitable for CONVOTHERM for tray rack trolley L 55mm W 50mm thickness 15mm		
For models:	OD12.20, OD20.10, OD20.20, OS12.20, OS20.10, OS20.20, OSC12.20, OSC20.10, OSC20.20, OSP12.20, OSP20.10, OSP20.20		



1

vm nr.	514441	Ref. No.	6015040 6056350
description	gasket suitable for CONVOTHERM L 65mm W 55mm thickness 2.5mm		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



springs

miscellaneous



1

vm nr.	697940	Ref. No.	5009083
description	spring for thermostat shaft diameter 6x4.6mm ømm L 35mm W 20mm H 9mm wire gauge ø 1mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		



1

vm nr.	697939	Ref. No.	5009082
description	spring for timer shaft diameter 6x4.6mm		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10		

manometers



1

vm nr.	541508	Ref. No.	6006140
description	manometer ø 40mm pressure range 0-4bar connection thread 1/8"		
For models:	OD10.10, OD10.20, OD12.20, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

hose reels and spray guns

spray guns



1

vm nr.	542964	Ref. No.	6011010
description	spray gun for appliances 1/2" ET L 135mm		
For models:	OEB10.10, OEB10.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS6.10, OGS6.20		




1

vm nr.	542038	Ref. No.	6011005
description	spray gun for appliances 3/8" IT L 135mm		



1

vm nr.	542376	Ref. No.	6056382
description	spray gun for appliances 3/8" L 125mm SS		



1

vm nr.	520277	Ref. No.	7012071 7012072
description	shower hose connections 1/2" L 1500mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	OEB10.10, OEB10.20, OES10.10, OES10.20, OGB10.10, OGB10.20, OGS10.10, OGS10.20		



			
1			
vm nr.	520096	Ref. No.	7002070 7012073
description	shower hose connections 1/2" L 2000mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	HUD10.10, HUD12.20, HUD6.10, OD10.10, OD6.10, OS10.10, OS6.10, OSC10.10, OSC6.10, OSG12.20, OSP10.10, OSP6.10		

			
1			
vm nr.	520097	Ref. No.	7002071
description	shower hose connections 1/2" L 2200mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	HUD20.10, OD10.20, OD12.20, OD20.10, OD20.20, OS10.20, OS12.20, OS20.10, OSC10.20, OSC12.20, OSC20.10, OSP10.20, OSP12.20, OSP20.10		

			
1			
vm nr.	520098	Ref. No.	7002072
description	shower hose connections 1/2" L 2600mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	HUD20.20, OD20.20, OS20.20, OSC20.20, OSG20.20, OSP20.20		

			
1			
vm nr.	520968	Ref. No.	2625199
description	shower hose connections 3/8" L 1700mm connection 2: 12mm		

			
1			
vm nr.	540008	Ref. No.	6005006 6005006K
description	shower head connection 1/2" metal		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20...(Other models you can see in the webshop)		

			
1			
vm nr.	540961	Ref. No.	6011012
description	wall holder for hand spray		
For models:	OEB10.10, OEB10.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS6.10, OGS6.20		

hose reels

appliance hose reels

			
1			
vm nr.	542319	Ref. No.	2625201 6011015
description	hose reel complete with spray gun hose length 1.5m		

cleaning guns

spare parts and accessories

hoses

			
1			
vm nr.	699853	Ref. No.	7064050
description	hose ø DN13mm length 960 with clip t.max. 95°C approval FDA		

hoses

supply hoses

plastic/rubber hoses

			
1			
vm nr.	699853	Ref. No.	7064050
description	hose ø DN13mm length 960 with clip t.max. 95°C approval FDA		

pre-rinse hoses

PVC braided hoses



vm nr.	520277	Ref. No.	7012071 7012072
description	shower hose connections 1/2" L 1500mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	OEB10.10, OEB10.20, OES10.10, OES10.20, OGB10.10, OGB10.20, OGS10.10, OGS10.20		



vm nr.	520311	Ref. No.	7012080 7013073
description	shower hose connections 1/2" L 1800mm operating p. 10bar burst p. 18bar t.max. 60°C approval NSF		



vm nr.	520096	Ref. No.	7002070 7012073
description	shower hose connections 1/2" L 2000mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	HUD10.10, HUD12.20, HUD6.10, OD10.10, OD6.10, OS10.10, OS6.10, OSC10.10, OSC6.10, OSG12.20, OSP10.10, OSP6.10		



vm nr.	520097	Ref. No.	7002071
description	shower hose connections 1/2" L 2200mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	HUD20.10, OD10.20, OD12.20, OD20.10, OD20.20, OS10.20, OS12.20, OS20.10, OSC10.20, OSC12.20, OSC20.10, OSP10.20, OSP12.20, OSP20.10		



vm nr.	520098	Ref. No.	7002072
description	shower hose connections 1/2" L 2600mm PVC operating p. 10bar burst p. 30bar t.max. 60°C approval NSF rotary with fabric		
For models:	HUD20.20, OD20.20, OS20.20, OSC20.20, OSG20.20, OSP20.20		

industrial hoses

rubber hoses - Goldschlange®



vm nr.	530540	Ref. No.	7002032
description	pressure hose ID ø 13mm ED ø 21mm L 5m operating p. 30bar burst p. 90bar t.max. 100°C Qty 5m		


Niplaflex hoses



vm nr.	530561	Ref. No.	7002033
description	pressure hose ID ø 10mm ED ø 17mm L 5m thickness 3.5mm operating p. 10bar burst p. 30bar t.max. 110°C		

PVC hoses


PVC braided hoses




vm nr.	530565	Ref. No.	7002031
description	PVC braided hose ID ø 13mm ED ø 19mm L 10m operating p. 10bar burst p. 30bar t.max. 60°C Qty 10m		

silicone hoses

without fabric



vm nr.	530479	Ref. No.	7012300 7012300K 7030646
description	silicone hose ID ø 10mm ED ø 16mm L 0.45m thickness 2.5mm operating pressure without pressure burst pressure non defined t.max. 200°C transparent drain cable ties		
For models:	OEB10.10, OEB6.10, OES10.10, OES6.10, OGB10.10, OGB6.10, OGS10.10, OGS6.10		

			
1			
vm nr.	530823	Ref. No.	7002012
description	silicone hose ID ø 12mm ED ø 16mm L 1m thickness 2mm operating pressure without pressure burst pressure non defined t.max. 200°C transparent		

formed hoses

straight

			
1			
vm nr.	694648	Ref. No.	7002015 7012305
description	hose ext. ø 20 D1 ø 15mm L 1080mm silicone for combi-steamer black		
For models:	OD10.20, OD12.20		

			
1			
vm nr.	699241	Ref. No.	7012003
description	hose ID ø 45mm ext. ø 55 L 800mm for ventilation		

form L

			
1			
vm nr.	506274	Ref. No.	5064082
description	formed hose end piece A ext. ø 28mm end piece A int. ø 22mm AD2 ø 28mm ø end piece B 22mm L 555mm boiler silicone combi-steamer L-shape white		

			
1			
vm nr.	699237	Ref. No.	6015100 6015100K 6030644
description	formed hose ext. ø 58 ID ø 48mm ED ø 37.5mm L 164mm for combi-steamer		

			
1			
vm nr.	530082	Ref. No.	6006201
description	formed hose ID ø 48mm ED ø 54mm L 110mm black Qty 1 L-shape for combi-steamer		
For models:	OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

			
1			
vm nr.	699367	Ref. No.	6064052
description	formed hose int. ø 1 47mm int. ø 2 30mm ED ø 54mm ext. ø 36 L 100mm for combi-steamer		

			
1			
vm nr.	530897	Ref. No.	2364047
description	hose ID ø 10mm ED ø 15mm for boiler suitable for combi-steamer CONVOTHERM 4		

fittings, hose and pipe connectors

hose connectors

without screw connection

			
1			
vm nr.	362001	Ref. No.	6005414 6064159
description	hose connector plastic hose ø 6-6mm		



hose connectors

plastic



1

vm nr.	361690	Ref. No.	6005423
description	hose connector plastic straight thread 1/8" hose ø 6mm Qty 1 pcs		



1

vm nr.	361754	Ref. No.	6005416
description	hose connector plastic angled thread 1/8" hose ø 6mm Qty 1 pcs		



1

vm nr.	520059	Ref. No.	6006076
description	hose connector plastic angled thread 3/4" hose ø 13mm Qty 5 pcs		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OS10.10, OS10.20, OS12.20, OS20.10, OS20.20, OS6.10, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSP10.10, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		

producer-specific



1

vm nr.	506242	Ref. No.	6014000
description	hose connector ID ø 12/6mm plastic L 195mm ø 16/10mm for combi-steamer		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		



1

vm nr.	501377	Ref. No.	6014001
description	hose connector ID ø 6mm L 96mm ø 10mm for combi-steamer		
For models:	OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

valves and tank inlets

ball valves

universal

ball valves with lever handle



1

vm nr.	520283	Ref. No.	6006074
description	ball valve connection 1/2" IT - 1/2" ET DN15 total length 59mm with lever handle handle length 85mm		

water cycle components

pressure reduction valves

pressure reduction valves

producer-specific



1

vm nr.	520993	Ref. No.	2226366 2230014
description	pressure reduction valve Norgren series R91 connection 1/8" nozzle ø 0.6mm setting range 0.1-2bar p max 10bar t.max. 50°C brass		
spare parts for	520993		
	vm nr.	541508	Ref. No. 6006140
	manometer ø 40mm pressure range 0-4bar connection thread 1/8"		
	vm nr.	541806	Ref. No. 5009061 5009063
	pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"		




1

vm nr.	520992	Ref. No.	2230015
description	pressure reduction valve Norgren series R91 connection 1/8" nozzle ø 0.7mm setting range 0.1-2bar p max 10bar t.max. 50°C brass		
spare parts for	520992		
	vm nr.	541508	Ref. No. 6006140
	manometer ø 40mm pressure range 0-4bar connection thread 1/8"		
	vm nr.	541806	Ref. No. 5009061 5009063
	pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"		



1

vm nr.	521052	Ref. No.	2230017
description	pressure reduction valve Norgren series R91 connection hose ø10mm default settingbar setting range 0.3-3.5bar p max 10bar t.max. 50°C with hose connection brass connection 10mm		



1

vm nr.	521047	Ref. No.	2226365 2230013
description	pressure reduction valve Norgren series R91 connection hose ø10mm default settingbar setting range 0.3-3.5bar p max 10bar t.max. 50°C with hose connector and nozzle brass input pressure max. 10bar output pressure max. 3.4bar type R91W-2GK-NEN with pressure switch and monometer connection 10mm		
spare parts for	521047		
	vm nr.	541508	Ref. No. 6006140
	manometer ø 40mm pressure range 0-4bar connection thread 1/8"		
	vm nr.	541806	Ref. No. 5009061 5009063
	pressure control ø 38mm pressure range 0.2-3.0bar connection 1/8" 250V 10A GP600 pressure connection 1/8"		

supply filters



1

vm nr.	520262	Ref. No.	6006061
description	supply filter thread 3/4" IT - 3/4" IT total length 70mm red brass DN20 mesh opening 0.4mm		

non-return valves



1

vm nr.	531322	Ref. No.	6056934
description	backflow preventer for boiler L 88mm connection 10.5/13.5 hose ø 3/4"mm for combi-steamer CONVOTHERM 4		

ancillary products

PTFE tapes



1

vm nr.	890100	Ref. No.	7004052
description	PTFE tape reel L 12m W 12mm -200 up to +260°C approval DIN-DVGW, KTW temperature-resistant, elastic for fine thread thickness 0.1mm		
description	PTFE thread sealing tape for fine metal threads Application: All sanitary and heating circuits in hot and cold water areas. DVGW tested. DIN EN751-3. For fine thread DN < 10. Pressure: up to 20 bar. Temperature range: -60°C to +260°C		

thread sealants



1

vm nr.	890097	Ref. No.	7004016
description	thread sealing LOCTITE 577 medium-strength bottle 50ml pipe thread sealing t.max. 150°C approval BAM and DVGW		
description	LOCTITE® 577™ - bottle 50ml It is designed for the locking and sealing of metal pipes and fittings as well as other cylindrical metal assemblies. The product provides an instant, low-pressure seal for metal pipes and fittings. It will not creep, shrink or block systems by shredding. Suitable for fast application at low temperatures. It has excellent chemical and thermal resistance and offers less migration of liquid product after application to the part.		

silicone

food-grade silicones



1

vm nr.	890106	Ref. No.	7004020
description	silicone TB40 transparent tube 90g -40 up to +160°C		
description	Tomabond - TB40 - tube 90g - transparent For flexible sealing in drinking water, food, water and industrial kitchen areas. Securely joins glass, metal, wood-based materials, ceramic and plastics with high adhesion (1.1 N/mm²). Fungicide-, algicide- and solvent-free, ageing-resistant. Temperature-resistant from -40 °C to +160 °C Tested and approved by KTW / KSW.		
For models:	AR100, AR108, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		

clamps

hose clamps

DIN 3017 - W2



1

vm nr.	520112	Ref. No.	6006086
description	hose clamp ø 12-20mm width 9mm Qty 10 pcs DIN 3017		



1

vm nr.	520115	Ref. No.	6006087
description	hose clamp ø 25-40mm width 9mm Qty 10 pcs DIN 3017		

double wire clamps



1

vm nr.	505348	Ref. No.	8009058
description	wire clamp ø 9.8-10.4mm wire gauge ø 1.2mm zinc-coated steel Qty 100 pcs		

tools

hand tools

pullers



1

vm nr.	802191	Ref. No.	7015200
description	puller for fan wheel seat ø 28/34mm thread M16x1.5 WS 17		



fastening material

spacers

			
1			
vm nr.	551407	Ref. No.	8056358
description	mounting set control PCB M4 suitable for CONVOTHERM 4		

screws

countersunk screws

			
1			
vm nr.	699832	Ref. No.	8010001
description	countersunk screw thread M6 L 30mm SS DIN 7991/ISO 10642 Qty 1 pcs intake hexagonal		

flat-headed bolts

			
1			
vm nr.	560067	Ref. No.	8001031
description	flat-headed bolt thread M5 thread L 10mm SS DIN 7985/ISO 7045 Qty 20 pcs intake Phillips head ø 8mm head thickness 2mm		

hexagonal screws

			
1			
vm nr.	560083	Ref. No.	8003095
description	hexagonal screw thread M5 thread L 10mm SS WS 8 Qty 20 pcs DIN 933 / ISO 4017		

cylinder head bolts

DIN 912/ISO 4762

			
1			
vm nr.	560316	Ref. No.	8013002
description	cylinder head bolt thread M8 thread L 25mm WS 6 SS Qty 20 pcs DIN 912/ISO 4762		

side bolts

			
1			
vm nr.	699833	Ref. No.	8015000
description	side bolts thread M6 L 8mm DIN 916/ISO 4029 intake hexagonal		

nuts

hexagonal nuts

DIN 934 / ISO 4032/8673

			
1			
vm nr.	560129	Ref. No.	8017010
description	hexagonal nut thread M5 H 4mm WS 8 SS DIN/ISO DIN 934 / ISO 4032/8673 Qty 1 pcs		

fasteners

cable ties

			
1			
vm nr.	550254	Ref. No.	4007087
description	cable tie W 3.6mm L 140mm white Qty 100 pcs nylon		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20		

clamps

hose clamps

DIN 3017 - W2

			
1			
vm nr.	520112	Ref. No.	6006086
description	hose clamp ø 12-20mm width 9mm Qty 10 pcs DIN 3017		

			
1			
vm nr.	520115	Ref. No.	6006087
description	hose clamp ø 25-40mm width 9mm Qty 10 pcs DIN 3017		

double wire clamps



1

vm nr.	505348	Ref. No.	8009058
description	wire clamp ø 9.8-10.4mm wire gauge ø 1.2mm zinc-coated steel Qty 100 pcs		

consumables

sealants and adhesives

food-grade silicones



1

vm nr.	890106	Ref. No.	7004020
description	silicone TB40 transparent tube 90g -40 up to +160°C		
description	Tomabond - TB40 - tube 90g - transparent For flexible sealing in drinking water, food, water and industrial kitchen areas. Securely joins glass, metal, wood-based materials, ceramic and plastics with high adhesion (1.1 N/mm²). Fungicide-, algicide- and solvent-free, ageing-resistant. Temperature-resistant from -40 °C to +160 °C. Tested and approved by KTW / KSW.		
For models:	AR100, AR108, HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		

screw fixings



1

vm nr.	890063	Ref. No.	7004008 7004012
description	screw fixing LOCTITE 270 bottle 10ml high-strength		
description	LOCTITE® 270™ - bottle 10ml It is designed for the permanent locking and sealing of threaded fasteners. The product cures when confined in the absence of air between close fitting metal surfaces and prevents loosening and leakage from shock and vibration. LOCTITE® 270™ is particularly suited for heavy duty applications such as studs into motor housings, nuts onto studs in pump housings and other fasteners where high strength is required. LOCTITE® 270™ provides robust curing performance. It not only works on active metals (e.g. brass, copper) but also on passive substrates such as stainless steel and plated surfaces. The product offers high temperature performance and oil tolerance. It tolerates minor surface contaminations from various oils, such as cutting, lubrication, anti-corrosion and protection fluids.		
For models:	OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSG10.10, OSG12.20, OSG6.10		

thread sealants



1

vm nr.	890097	Ref. No.	7004016
description	thread sealing LOCTITE 577 medium-strength bottle 50ml pipe thread sealing t.max. 150°C approval BAM and DVGW		
description	LOCTITE® 577™ - bottle 50ml It is designed for the locking and sealing of metal pipes and fittings as well as other cylindrical metal assemblies. The product provides an instant, low-pressure seal for metal pipes and fittings. It will not creep, shrink or block systems by shredding. Suitable for fast application at low temperatures. It has excellent chemical and thermal resistance and offers less migration of liquid product after application to the part.		

PTFE tapes



1

vm nr.	890100	Ref. No.	7004052
description	PTFE tape reel L 12m W 12mm -200 up to +260°C approval DIN-DVGW, KTW temperature-resistant, elastic for fine thread thickness 0.1mm		
description	PTFE thread sealing tape for fine metal threads Application: All sanitary and heating circuits in hot and cold water areas. DVGW tested. DIN EN751-3. For fine thread DN < 10. Pressure: up to 20 bar. Temperature range: -60°C to +260°C		

lubricants

graphite paste



1

vm nr.	890006	Ref. No.	7014005
description	graphite paste FERMIT NIVO can 500g		
description	Fermit NIVO - can 500g Highly refractory sealing paste for threaded and flanged joints Prevents the sticking of gaskets, bolts, screws etc. which are exposed to intense heat. In the case of flange gaskets and surface seals, coat both sides with the paste. In the case of use as sealants for threads (DIN 2999) at over 160 degrees C, the use of aluminium hemp with Nivo Graphite Paste is recommended as normal hemp becomes scaly at these temperatures and then leaks can occur. Temperature range: 0°C to + 300°C		

cleaning agents

combi-steamer detergents/descalers

Notice: Articles labelled 'DANGEROUS GOODS' are delivered by road through a forwarder for reasons of safety and are charged separately!



1

vm nr.	890032	Ref. No.	3007014 3007017
description	detergent Convoclean forte 10L		
description			
For models:	OS12.20, OS20.10, OS20.20		



1

vm nr.	802066 ¹	Ref. No.	3007028
description	detergent for combi-steamer CONVOTHERM CONVOCare nozzle detergent 1l concentrate P2 P3 concentrate mixing ratio 1:29 1l		
description	Convotherm ConvoCare K - bottle 1 litre For preventing and dissolving limescale deposits. Particularly suitable in regions with very hard water. Through the use of liquid detergents no residue remains in the cooking chamber. The environment is also considered - all products are compliant with the ISO standard and are biologically degradable. - 1l concentrate - rinse aid for CONVOClean system - must be mixed with water in a ratio of 1:29		
For models:	OEB6.10, OES6.10, OS12.20, OS20.10, OS20.20		

¹DANGEROUS GOODS

descalers



1

vm nr.	802196	Ref. No.	3007023
description	descaler ConvCal forte 10l		




1

vm nr.	802195	Ref. No.	3007018
description	descaler ConvoCal for combi-steamer 10l		

fuses

fine fuses



1

vm nr.	358600	Ref. No.	4005064
description	fine fuse size 1A slow-acting rated 250V Qty 10 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.06, OES6.10, OES6.20, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10, OSP10.10, OSP10.20, OSP12.20... (Other models you can see in the webshop)		



1

vm nr.	358603	Ref. No.	4005066 4056944
description	fine fuse size 2A slow-acting rated 250V Qty 10 pcs		
For models:	AR108, AR12, AR18, AR28, AR40, AR54, AR72, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OEB10.10, OEB10.20, OEB12.20, OEB20.10, OEB20.20, OEB6.10, OEB6.20, OES10.10, OES10.20, OES12.20, OES20.10, OES20.20, OES6.10, OES6.20, OGB10.10, OGB10.20, OGB12.20, OGB20.10, OGB20.20, OGB6.10, OGB6.20, OGS10.10, OGS10.20, OGS12.20, OGS20.10, OGS20.20, OGS6.10, OGS6.20, OSC10.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSC6.10, OSG10.10, OSG12.20, OSG20.20... (Other models you can see in the webshop)		



1

vm nr.	358605	Ref. No.	4056945
description	fine fuse size 3.15A slow-acting rated 250V Qty 10 pcs		



1

vm nr.	358607	Ref. No.	4005068
description	fine fuse size 6.3A slow-acting rated 250V Qty 10 pcs		
For models:	HUD10.10, HUD12.20, HUD20.10, HUD20.20, HUD6.10, OD10.10, OD10.20, OD12.20, OD20.10, OD20.20, OD6.10, OSG10.10, OSG12.20, OSG20.20, OSG6.10		

ø6.3x32mm 500V



1

vm nr.	358751	Ref. No.	4005069
description	fine fuse size 6.3A fast-acting rated 500V Qty 10 pcs		

screw locks

D0-system (NEOZED)



1

vm nr.	358073	Ref. No.	4005053
description	fuse size D01 10A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		



1

vm nr.	358043	Ref. No.	4005054
description	fuse size D01 16A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	HUD12.20, HUD20.10		



1

vm nr.	358070	Ref. No.	4005050
description	fuse size D01 2A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	AR100, AR108, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		



1

vm nr.	358071	Ref. No.	4005051
description	fuse size D01 4A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	AR100, AR108, AR30, AR40, AR50, AR54, AR72, OES12.20, UG10.10, UG20.10, UG6.10		

			
1			
vm nr.	358072	Ref. No.	4005052
description	fuse size D01 6A rated 250/400V E14 ø 11mm L 36mm Qty 10 pcs		
For models:	OEB20.20, UG20.20		

			
1			
vm nr.	358048	Ref. No.	4005058
description	fuse size D02 20A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	AR108, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10		

			
1			
vm nr.	358044	Ref. No.	4005046 4005055
description	fuse size D02 25A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	AR100, AR108, HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, UG10.20		

			
1			
vm nr.	358045	Ref. No.	2212003 4005056
description	fuse size D02 35A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	HUD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OES20.10, UG20.10, UG20.20		

			
1			
vm nr.	358046	Ref. No.	4005057
description	fuse size D02 50A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20		

			
1			
vm nr.	358047	Ref. No.	4005059
description	fuse size D02 63A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		
For models:	OEB20.10, OES20.10		

gauge pieces (NEOZED)			
			
1			
vm nr.	358055	Ref. No.	4005013
description	gauge piece size D01 suitable for 10A		

			
1			
vm nr.	358052	Ref. No.	4005010
description	gauge piece size D01 suitable for 2A		
For models:	AR100, AR108, AR16, AR18, AR28, AR30, AR40, AR50, AR54, AR72, UG10.10, UG10.20, UG20.10, UG20.20, UG6.05, UG6.10		

			
1			
vm nr.	358053	Ref. No.	4005011
description	gauge piece size D01 suitable for 4A		
For models:	AR100, AR108, AR30, AR40, AR50, AR54, AR72, OES12.20, OES20.20, UG10.10, UG20.10, UG6.10		

			
1			
vm nr.	358054	Ref. No.	4005012
description	gauge piece size D01 suitable for 6A		
For models:	UG20.20		

			
1			
vm nr.	358064	Ref. No.	4005021
description	gauge piece size D02 suitable for 16A		
For models:	OD10.20, OD12.20, OD20.10, OSP10.20, OSP12.20		



1

vm nr.	358065	Ref. No.	4005014
description	gauge piece size D02 suitable for 20A		
For models:	AR108, HUD12.20, HUD20.10, HUD20.20, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20, OSP6.10		



2

vm nr.	358066	Ref. No.	4005015
description	gauge piece size D02 suitable for 25A		
For models:	AR100, AR108, OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20, UG10.20		



1

vm nr.	358067	Ref. No.	4005016
description	gauge piece size D02 suitable for 35A		
For models:	HUD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.10, OES20.10, OSC20.20, OSP20.20, UG20.10, UG20.20		



1

vm nr.	358068	Ref. No.	4005017
description	gauge piece size D02 suitable for 50A		
For models:	OD10.20, OD12.20, OD20.10, OD20.20, OEB10.20, OEB12.20, OEB20.20, OES10.20, OES12.20, OES20.20, OSC10.20, OSC12.20, OSC20.10, OSC20.20, OSP10.20, OSP12.20, OSP20.10, OSP20.20		

A

alarm devices	15
appliance hose reels	73
axial fans	28

B

ball valves	76
bi-metal thermostats	7, 7

C

cable ties	79
cables	36
cam switches	9
castors and bumper angles	64
clamps	78, 79
cleaning agents	81
cleaning guns	73
combi-steamer detergents/descalers	81
condensators & interference suppression filters	32
connection cables	36
consumables	80
contactors	15
control equipment	10
control thermostats	7
countersunk screws	79
cylinder head bolts	79

D

descalers	81
door seals	65
double wire clamps	78, 80
drain pumps	32

E

electric accessories	36
electrodes	27

F

fans	28
fasteners	79
fastening material	79
filters	32
fine fuses	82
flat-headed bolts	79
flow sensors	27
food-grade silicones	78, 80
forced air burners	46
formed hoses	75
fuses	33, 82

G

gas burners	46
-------------	----

gas control valves	42
gas nozzles	46
gaskets for control panels	68
gaskets for heated units	64
gaskets for tray rack trolleys	68
graphite paste	81

H

hand tools	78
heating elements	2
heating elements for convection	4
hexagonal nuts	79
hexagonal screws	79
hose clamps	78, 79
hose connectors	75, 76
hose reels	73
hoses	73, 73
hot air fans	31
hot air motors	28

I

ignition boxes	44
ignition cables	46
immersion heating elements	2
indicator lights	11
indicator lights (complete)	11
industrial hoses	74

L

lamps	11
light bulbs	11
lubricants	81

M

magnetic switches	9
mechanical timers	14
motors	32

N

Niplaflex hoses	74
non-return valves	77
nuts	79

O

O-rings	69
oven lamps	12
overlying hinges	62

P

piano hinges	62
pilot burners	44
plastic/rubber hoses	73
pre-rinse hoses	74

pressure reduction valves	76, 76
pressure switches	26
probes	18
PTFE tapes	47, 77, 81
pullers	78
pumps	32
PVC braided hoses	74
PVC hoses	74

R

radial fans	31
relays	17
rubber hoses - Goldschlange®	74

S

safety thermostats	7
screw fixings	80
screw locks	82
screws	79
sealants and adhesives	80
sealing washers	69
shaft gaskets	70
side bolts	79
silicone	78, 80
silicone hoses	74
solenoid valves	23
solid state relays	17
spray guns	72
spray guns with external thread	72
supply filters	77, 77
supply hoses	73
switches and momentary switches	9

T

terminals	36
thermocouples	46
thermostats	7
thread sealants	47, 78, 80
timers	14
tools	78
transformers	18
turning lever locks	58

V

valves and tank inlets	76
vibration pumps	32

W

wash and rinse pumps	32
water cycle components	76
window seals	64